



| FEATURES | BENEFITS |
|--|--|
| <ul style="list-style-type: none"> • Integral terminations • Clicks when connected • Compatibility • CPC thumb latch | <ul style="list-style-type: none"> • Fewer leak points, shorter assemblies, faster installations • Assurance of a reliable connection • Mates with MC & PMC12 Series couplings • One hand connection & disconnection |
| SPECIFICATIONS | |
| Bodies & valves | Acetal |
| Internal spring | 316 stainless steel |
| External springs, pin, latch | Stainless steel |
| Seal material | NBR |
| Colour | Natural white |
| Working pressure | Vacuum to 120 psi (8.3 bar) |
| Operating temperature | -40°C to +82°C (-40°F to +180°F) |



Min. quantities may apply – please ask at time of ordering

COUPLING BODIES

PIPE THREAD – VALVED

NPT MALE



800

| PART NUMBER | THREAD |
|-------------|----------|
| cPMCD10-02 | 1/8" NPT |
| cPMCD10-04 | 1/4" NPT |

BSPT MALE

| | |
|-------------|-----------|
| cPMCD10-020 | 1/8" BSPT |
| cPMCD10-040 | 1/4" BSPT |

UNVALVED

NPT MALE

| | |
|-----------|----------|
| cPMC10-02 | 1/8" NPT |
| cPMC10-04 | 1/4" NPT |

BSPT MALE

| | |
|------------|-----------|
| cPMC10-020 | 1/8" BSPT |
| cPMC10-040 | 1/4" BSPT |

IN-LINE – VALVED

HOSE BARB



800

| PART NUMBER | TUBE ID | METRIC EQ. |
|-------------|---------|------------|
| cPMCD17-01 | 1/16" | 1.6 mm |
| cPMCD17-02 | 1/8" | 3.2 mm |
| cPMCD17-03 | 3/16" | 4.8 mm |
| cPMCD17-04 | 1/4" | 6.4 mm |

UNVALVED

| | | |
|-----------|-------|--------|
| cPMC17-01 | 1/16" | 1.6 mm |
| cPMC17-02 | 1/8" | 3.2 mm |
| cPMC17-03 | 3/16" | 4.8 mm |
| cPMC17-04 | 1/4" | 6.4 mm |

IN-LINE – VALVED FERRULESS POLYTUBE FITTING, PTF



800

| PART NUMBER | TUBE OD | TUBE ID | METRIC EQ. |
|-------------|---------|---------|--------------|
| cPMCD13-M42 | – | – | 4 x 2 mm |
| cPMCD13-025 | 5/32" | 0.10" | 4 x 2.5 mm |
| cPMCD13-04 | 1/4" | 0.17" | 6.4 x 4.3 mm |

UNVALVED

| | | | |
|------------|-------|-------|--------------|
| cPMC13-M42 | – | – | 4 x 2 mm |
| cPMC13-025 | 5/32" | 0.10" | 4 x 2.5 mm |
| cPMC13-04 | 1/4" | 0.17" | 6.4 x 4.3 mm |

Also available NSF listed

IN-LINE – VALVED

UNF FEMALE



800

| PART NUMBER | THREAD |
|--------------|-----------|
| cPMCD19-1032 | 10-32 UNF |

UNVALVED

| | |
|-------------|-----------|
| cPMC19-1032 | 10-32 UNF |
|-------------|-----------|

PANEL MOUNT – VALVED

HOSE BARB



800

| PART NUMBER | TUBE ID | METRIC EQ. |
|-------------|---------|------------|
| cPMCD16-01 | 1/16" | 1.6 mm |
| cPMCD16-02 | 1/8" | 3.2 mm |
| cPMCD16-03 | 3/16" | 4.8 mm |
| cPMCD16-04 | 1/4" | 6.4 mm |

UNVALVED

| | | |
|-----------|-------|--------|
| cPMC16-01 | 1/16" | 1.6 mm |
| cPMC16-02 | 1/8" | 3.2 mm |
| cPMC16-03 | 3/16" | 4.8 mm |
| cPMC16-04 | 1/4" | 6.4 mm |

PANEL MOUNT – VALVED

FERRULESS POLYTUBE FITTING, PTF



800

| PART NUMBER | TUBE OD | TUBE ID | METRIC EQ. |
|-------------|---------|---------|--------------|
| cPMCD12-M42 | – | – | 4 x 2 mm |
| cPMCD12-025 | 5/32" | 0.10" | 4 x 2.5 mm |
| cPMCD12-04 | 1/4" | 0.17" | 6.4 x 4.3 mm |

UNVALVED

| | | | |
|------------|-------|-------|--------------|
| cPMC12-M42 | – | – | 4 x 2 mm |
| cPMC12-025 | 5/32" | 0.10" | 4 x 2.5 mm |
| cPMC12-04 | 1/4" | 0.17" | 6.4 x 4.3 mm |

PANEL MOUNT – VALVED

UNF FEMALE



800

| PART NUMBER | THREAD |
|--------------|-----------|
| cPMCD18-1032 | 10-32 UNF |

UNVALVED

| | |
|-------------|-----------|
| cPMC18-1032 | 10-32 UNF |
|-------------|-----------|