


NYLON AIRLINE RECOILS

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> <li>Compressed air</li> <li>Water</li> <li>Oil / fuel</li> </ul>	<ul style="list-style-type: none"> <li>Excellent flexibility</li> <li>Mirror smooth inner layer for improved flow</li> <li>Lightweight</li> <li>Excellent kink prevention</li> <li>Produced to exacting tolerances</li> </ul>
SPECIFICATIONS	
Temperature range	-40°C to +80°C
Pressure rating	15 bar (218 psi)
Construction	Virgin polymer type 12. Complete with 360° swivel BSPT compression couplings & spring.
Applicable standards	BS5409:1976



**EC – RED**  
BSPT FITTINGS  
76 MM MANDREL SIZE

1150



**EC – BLUE**  
BSPT FITTINGS  
76 MM MANDREL SIZE

1150

PART NUMBER	Ø	Ø	Ø	Ø
EC08WF025R	8	6	2.5	1/4
EC08WF05R	8	6	5.0	1/4
EC08WF075R	8	6	7.5	1/4
EC08WF10R	8	6	10.0	1/4
EC08WF15R	8	6	15.0	1/4

76 MM MANDREL SIZE

EC10WF025R	10	8	2.5	1/4
EC10WF05R	10	8	5.0	1/4
EC10WF075R	10	8	7.5	1/4
EC10WF10R	10	8	10.0	1/4

90 MM MANDREL SIZE

EC12WF025R	12	9	2.5	3/8
EC12WF05R	12	9	5.0	3/8
EC12WF075R	12	9	7.5	3/8
EC12WF10R	12	9	10.0	3/8

PART NUMBER	Ø	Ø	Ø	Ø
EC08WF025BL	8.0	6.0	2.5	1/4
EC08WF05BL	8.0	6.0	5.0	1/4
EC08WF075BL	8.0	6.0	7.5	1/4
EC08WF10BL	8.0	6.0	10.0	1/4
EC08WF15BL	8.0	6.0	15.0	1/4

76 MM MANDREL SIZE

EC10WF025BL	10.0	8.0	2.5	1/4
EC10WF05BL	10.0	8.0	5.0	1/4
EC10WF075BL	10.0	8.0	7.5	1/4
EC10WF10BL	10.0	8.0	10.0	1/4

90 MM MANDREL SIZE

EC12WF025BL	12.0	9.0	2.5	3/8
EC12WF05BL	12.0	9.0	5.0	3/8
EC12WF075BL	12.0	9.0	7.5	3/8
EC12WF10BL	12.0	9.0	10.0	3/8

**Do you also need?**

**Blow guns**

Find it on pages 726 – 742, section twelve