

SILICONE TUBE

PARKAIR[®]

REINFORCED SILICONE TUBE

| SUITABILITY | | FEATURES / BENEFITS | | |
|--|--|---|--|--|
| Food & beverages Pharmaceutical processing Laboratory uses | | Made from raw materials that are FDA & WRC approved Weather & ozone resistant Peroxide cured | | |
| SPECIFICATIONS | | | | |
| Temperature range | -40°C to +180°C | | | |
| Pressure rating | Values given are based on the short term burst pressure of PSILB hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values. | | | |
| Construction | Translucent silicone rubber tube 70° shore, A ± 5° shore. Reinforced with polyester fibre yarn. | | | |
| | | | | |

| PSILB – TRANSLUCENT 25 METRE COILS | | | 1444 | 7600 | |
|---------------------------------------|-------------|------|------|-------|--|
| | PART NUMBER | | ins | (Car) | |
| | PSILB 3.0 | 3.0 | 1/8 | 5 | |
| | PSILB 5.0 | 5.0 | 3/16 | 6 | |
| | PSILB 6.0 | 6.0 | 1/4 | 7 | |
| | PSILB 8.0 | 8.0 | 5/16 | 10 | |
| | PSILB 9.5 | 9.5 | 3/8 | 10 | |
| | PSILB 12.5 | 12.5 | 1/2 | 6 | |
| | PSILB 16.0 | 16.0 | 5/8 | 6 | |
| | PSILB 19.0 | 19.0 | 3/4 | 5 | |
| | PSILB 25.0 | 25.0 | 1 | 5 | |



UNREINFORCED SILICONE TUBE

SUITABILITY

Food & beverages

- Pharmaceutical processing
- Laboratory usesThermal protection
- · mermai protectio

SPECIFICATIONS

Construction



FEATURES / BENEFITS

Made from raw materials that are FDA & WRC approved
 Peroxide cured

Temperature range -40°C to +180°C

Translucent silicone rubber tube 60° shore, A $\pm 5^{\circ}$ shore. Talc free.

| TRANSLUCENT 25 METRE COILS | | | | 7600 |
|-------------------------------|----|-----|--------------|------|
| PART NUMBER | | | \mathbb{H} | |
| PSIL3x1 | 3 | 1.0 | 5.0 | |
| PSIL3x2 | 3 | 2.0 | 7.0 | |
| PSIL4x2 | 4 | 2.0 | 8.0 | |
| PSIL5x1.5 | 5 | 1.5 | 8.0 | |
| PSIL5x2.5 | 5 | 2.5 | 10.0 | |
| PSIL6x2 | 6 | 2.0 | 10.0 | |
| PSIL8x2 | 8 | 2.0 | 12.0 | |
| PSIL8x2.4 | 8 | 2.4 | 12.8 | |
| PSIL8x3 | 8 | 3.0 | 14.0 | |
| PSIL9x2 | 9 | 2.0 | 13.0 | |
| PSIL9x3 | 9 | 3.0 | 15.0 | |
| PSIL10x2 | 10 | 2.0 | 14.0 | |
| PSIL16x3 | 16 | 3.0 | 22.0 | |
| PSIL19x3 | 19 | 3.0 | 25.0 | |

Ten

SUITABILITY

- Food & beverages
- Pharmaceutical processing
- Laboratory uses
- Thermal protection

SPECIFICATIONS Temperature range

Construction



FEATURES / BENEFITS

 Made from raw materials that are FDA & WRC approved

Peroxide cured

-40°C to +180°C

Translucent silicone rubber tube 60° shore, A \pm 5° shore. Talc free.

| PSIL TRANSLUCENT 25 METRE COILS | | | | 7600 |
|---------------------------------------|------|-------|--------------|------|
| PART NUMBER | ins | (inc) | \mathbb{O} | |
| PSIL16/16 | 1/16 | 1/16 | 3/16 | |
| PSIL18/16 | 1/8 | 1/16 | 1/4 | |
| PSIL14/16 | 1/4 | 1/16 | 3/8 | |
| PSIL38/18 | 3/8 | 1/8 | 5/8 | |
| PSIL12/18 | 1/2 | 1/8 | 3/4 | |