

## REINFORCED ANTISTATIC EPDM RUBBER HOSE

### FEATURES

- Dissipates electro-static discharge & minimises errant sparks
- Excellent weather resistance
- Extreme flexibility
- Electrically conductive

### SPECIFICATIONS

|                   |                     |
|-------------------|---------------------|
| Temperature range | -30°C to +60°C      |
| Construction      | Braided EPDM rubber |

Supplied in full coils only



### REINFORCED ANTISTATIC EPDM RUBBER HOSE 40 METRE COILS

285

#### PART NUMBER

| C199009920 | 8.0  | 15.0 | 12 |
|------------|------|------|----|
| C199009918 | 10.0 | 17.5 | 12 |
| C199009921 | 12.0 | 19.5 | 12 |

## RUBBER ALLOY BREATHING AIR HOSE

### AIRTECH TPV – THERMOPLASTIC RUBBER BREATHING AIR HOSE

#### SUITABILITY

- Breathing air – superior flexibility without smell or taint
- All applications where enhanced flexibility & temperature performance are desirable

#### FEATURES / BENEFITS

- Compatible with a wide range of chemicals
- Lightweight & flexible for ease of use
- Thick hose wall to protect against crushing & kinking
- Virtually odourless
- DEHP & phthalate free
- High flexibility at low temperatures
- Can be supplied as an antistatic version.
- Working pressure can be specified up to 20 bar
- It accepts all standard fittings & can be clamped or swaged using standard equipment

#### SPECIFICATIONS

|                      |   |
|----------------------|---|
| Temperature range    | -30°C to +100°C   |
| Pressure rating      | Values given are based on the short term burst pressure of ATPPV hose at 20°C using a 3:1 safety factor.<br>NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values. |
| Construction         | TPV construction throughout for superior flexibility & lightness. Black outer cover with wide blue stripe & textile polyester reinforcement.  |
| Applicable standards | Manufactured in accordance with EN ISO5774.   |



### ATPPV – BLUE 25 METRE COILS

1352

#### PART NUMBER

| ATPPVAS06-25 | 6.3  | 11.0 | 2.35 | 20 |
|--------------|------|------|------|----|
| ATPPVAS08-25 | 8.0  | 13.5 | 2.75 | 20 |
| ATPPVAS10-25 | 10.0 | 16.0 | 3.00 | 20 |
| ATPPVAS13-25 | 13.0 | 21.0 | 3.00 | 20 |

### AIRTECH BR A/S – REINFORCED ANTISTATIC BREATHING AIR HOSE

#### SUITABILITY

- Spray paint booth
- Compressed air supply to individual protective apparatus
- Petrochemical industry
- Nuclear power plants

#### FEATURES / BENEFITS

- Antistatic inner layer
- Oil & grease resistant outer protective cover
- Excellent chemical resistance
- Decontamination proof

#### SPECIFICATIONS

|                      |  |
|----------------------|--|
| Temperature range    | -20°C to +70°C   |
| Pressure rating      | Values given are based on the short term burst pressure of ATAS hose at 20°C using a 3:1 safety factor.<br>NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values. |
| Construction         | Antistatic black inner wall with PVC intermediate layer, polyester fibre reinforcement layer & blue oil resistant PVC outer cover with wide yellow stripes.  |
| Applicable standards | EN 14593 & EN 14594 (EN139:1994 is superseded by EN14593 for demand valve apparatus & EN14594 for constant flow).  |



### ATBRAS – BLUE 25 METRE COILS

1352

#### PART NUMBER

| ATBRAS08-25 | 8.0  | 14.0 | 3.00 | 16 |
|-------------|------|------|------|----|
| ATBRAS10-25 | 10.0 | 16.0 | 3.00 | 16 |
| ATBRAS12-25 | 12.7 | 19.0 | 3.15 | 16 |