

RUBBER OIL / LEADED PETROL HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Industrial oils, fuel oils, diesel & petrol (including unleaded) Compressed air 	<ul style="list-style-type: none"> Good resistance to abrasion, oil mist & weather
SPECIFICATIONS	
Temperature range	-40°C to +80°C
Pressure rating	Values given are based on the short term burst pressure of H-OP hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black smooth NBR. Textile spirally laid reinforcement. CR/SBR cover.
Applicable standards	SAE J30R6

H-OP – BLACK 10 METRE COILS



6950

PART NUMBER



H-OP04	6	1/4	13	25
H-OP05	8	5/16	15	25
H-OP06	10	3/8	17	25
H-OP08	13	1/2	21	25
H-OP10	16	5/8	25	25
H-OP12	19	3/4	28	25
H-OP16	25	1	35	25

Supplied in full coils only

UNLEADED FUEL HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Conveyance of leaded or unleaded fuel 	
SPECIFICATIONS	
Temperature range	-20°C to +80°C
Pressure rating	Values given are based on the short term burst pressure of H-UFH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black NBR tube. High tensile synthetic fibre reinforcement. Black cover with high resistance to weather, heat & fuel.
Applicable standards	SAE J30R6

UFH – BLACK 10 METRE COILS



6950

PART NUMBER



H-UFH5/16	5	3/16	12	20
H-UFH6/13	6	1/4	13	20
H-UFH8/15	8	5/16	15	20
H-UFH10/17	10	3/8	17	20
H-UFH13/21	13	1/2	21	20

Supplied in full coils only

20 BAR DIESEL DROP HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Diesel, air, water delivery up to 20 bar 	
SPECIFICATIONS	
Temperature range	-10°C to +60°C
Pressure rating	Values given are based on the short term burst pressure of DDH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Oil resistant rubber alloy tube with synthetic textile braid reinforcement. Black weather & ozone resistant cover with purple stripe.

DDH – BLACK 50 METRE COILS



6950

PART NUMBER



DDH19/28	19	3/4	28	20
DDH25/34	25	1	34	20


Supplied in full coils only

FUEL HOSE

GALVANISED STEEL WIRE OVERBRAIDED FUEL HOSE

SUITABILITY	FEATURES / BENEFITS
<ul style="list-style-type: none"> Engine lubricants (HD-oils) Hydraulic fluids based upon mineral & glycol Diesel fuels Turpentine oil & substitute Vegetable lubricants Multi-purpose fuels, kerosene Refrigerants (glycol) glystantine Water Air 	<ul style="list-style-type: none"> 80°C 80°C 80°C 20°C 80°C 40°C 80°C 80°C 80°C
SPECIFICATIONS	
Construction	Synthetic rubber hose braided with galvanised steel wire.
Applicable standards	DIN 73 379C

FUEL HOSE



4700

PART NUMBER



S601-302	4.5	9.5	20
S601-304	5.5	10.5	20
S601-306	7.5	12.5	15
S601-308	9.0	14.0	15
S601-310	11.0	17.7	15
S601-313	14.0	21.2	15
S601-316	17.0	24.0	15
S601-320	21.5	30.0	15