


ORANGE COVER HOSE FOR LIQUIFIED PETROLEUM GASES

SUITABILITY	
• Conveying liquified petroleum gases	
SPECIFICATIONS	
Temperature range	-20°C to +80°C LPG
Pressure rating	Values given are based on the short term burst pressure of H-LPG hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black synthetic rubber tube. Synthetic textile reinforcement. Orange weather & flame resistant synthetic rubber cover.
Applicable standards	ISO3821

Supplied in full coils only

H-LPG – ORANGE
20 METRE COILS



6950


PART NUMBER				
H-LPG5/12ORA	5	3/16	12	20
H-LPG6/13ORA	6	1/4	13	20
H-LPG8/15ORA	8	5/16	15	20
H-LPG10/17ORA	10	3/8	17	20
H-LPG13/21ORA	13	1/2	21	20

WELDING HOSE FOR OXYGEN

SUITABILITY	
• Conveying oxygen	
SPECIFICATIONS	
Temperature range	-20°C to +90°C
Pressure rating	Values given are based on the short term burst pressure of H-OWH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black synthetic rubber tube. Synthetic textile reinforcement. Blue weather & flame resistant synthetic rubber cover.
Applicable standards	ISO3821

Supplied in full coils only

H-OWH – BLUE
20 METRE COILS



6950

PART NUMBER				
H-OWH6/13BLU	6	1/4	13	20
H-OWH8/15BLU	8	5/16	15	20
H-OWH10/17BLU	10	3/8	17	20
H-OWH13/21BLU	13	1/2	21	20

WELDING HOSE FOR ACETYLENE

SUITABILITY	
• Conveying acetylene	
SPECIFICATIONS	
Temperature range	-20°C to +90°C
Pressure rating	Values given are based on the short term burst pressure of H-AWH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black synthetic rubber tube. Synthetic textile reinforcement. Red weather & flame resistant synthetic rubber cover.
Applicable standards	ISO3821

Supplied in full coils only

H-AWH – RED
20 METRE COILS



6950

PART NUMBER				
H-AWH6/13RED	6	1/4	13	20
H-AWH8/15RED	8	5/16	15	20
H-AWH10/17RED	10	3/8	17	20
H-AWH13/21RED	13	1/2	21	20

SHOTBLAST HOSE

SUITABILITY	
• Shotblasting	
SPECIFICATIONS	
Temperature range	-40°C to +70°C
Pressure rating	Values given are based on the short term burst pressure of H-SBH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black high abrasion resistant, conductive, natural rubber tube. Synthetic textile fabric & one conductive copper wire reinforcement. Black, high abrasion, weather & ozone resistant SBR/EPDM rubber cover.
Applicable standards	ISO DIN53516

Supplied in full coils only

New Additions
H-SBH – BLACK
40 METRE COILS



6985

PART NUMBER				
H-SBH19/35-40	19	3/4	35	12
H-SBH25/39-40	25	1	39	12
H-SBH32/48-40	32	1 1/4	48	12
H-SBH32/54-40	32	1 1/4	54	12