

10 BAR WATER SUCTION & DELIVERY HOSE

SUITABILITY	
• Heavy duty water suction & delivery	
SPECIFICATIONS	
Temperature range	-40°C to +70°C
Pressure rating	Values given are based on the short term burst pressure of H-WSDH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black NR / SBR synthetic rubber tube. Reinforcement – synthetic textile & steel wire helix embedded between the layers. Black weather & ozone resistant SBR / EPDM rubber cover.

Supplied in full coils only

H-WSDH – BLACK
10 METRE COILS



6975


PART NUMBER				
H-WSDH32/42-10	32	1 1/4	42	10
H-WSDH38/48-10	38	1 1/2	48	10
H-WSDH51/62-10	51	2	62	10

10 BAR OIL SUCTION & DELIVERY HOSE

SUITABILITY	
• Heavy duty oil suction & delivery	
SPECIFICATIONS	
Temperature range	-20°C to +70°C
Pressure rating	Values given are based on the short term burst pressure of H-OSDH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Black smooth synthetic rubber tube, resistant to mineral oils & fuels with max. 50% aromatic content. Reinforcement – high tensile textile plies & embedded steel wire helix. Copper antistatic wire. Abrasion, oil, fuel, ozone & weather resistant.

Supplied in full coils only

H-OSDH – BLACK
10 METRE COILS



6975

PART NUMBER				
H-OSDH19/30-10	19	3/4	29	10
H-OSDH25/35-10	25	1	35	10
H-OSDH32/42-10	32	1 1/4	42	10
H-OSDH38/48-10	38	1 1/2	48	10
H-OSDH45/55-10	45	1 3/4	55	10
H-OSDH51/61-10	51	2	61	10

10 BAR UHMWPE CHEMICAL HOSE

SUITABILITY	
• Transfer of up to 90% of chemicals	
SPECIFICATIONS	
Temperature range	-30°C to +80°C
Pressure rating	Values given are based on the short term burst pressure of H-UHMWPE hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Chemical resistant, ultra high molecular polyethylene tube. Synthetic textile fabric, twin helix steel wire & one conductive copper wire reinforcement. Green, weather, ozone & chemical resistant EPDM rubber cover.

Supplied in full coils only

H-UHMWPE – GREEN
10 METRE COILS



6975

PART NUMBER				
H-UHMWPE/019	19	3/4	31	10
H-UHMWPE/025	25	1	37	10
H-UHMWPE/032	32	1 1/4	45	10
H-UHMWPE/038	38	1 1/2	51	10
H-UHMWPE/051	51	2	65	10

10 BAR BREWERS DELIVERY HOSE

SUITABILITY	
• Delivery of non fatty foods • Ideal for food quality applications	
SPECIFICATIONS	
Temperature range	-35°C to +70°C
Pressure rating	Values given are based on the short term burst pressure of H-BDH hose at 20°C using a 3:1 safety factor. NOTE: Any increase in temperature above 20°C will result in a decline in the working pressure values.
Construction	Orange FDA heat resistant NR rubber tube. Synthetic textile fabric reinforcement. Orange weather, ozone & heat resistant NR rubber cover.

Supplied in full coils only

H-BDH – ORANGE
10 METRE COILS



6975

PART NUMBER				
H-BDH25/38-10	25	1	38	10