

## FLEXIBLE NEOPRENE HOSE DUCTING



### WYREM® FLEXIBLE HOSE DUCTING 6 METRE LENGTH



6990

#### FEATURES / BENEFITS

- Offers high resistance to chemical attack in both acidic & basic solutions
- Cotton has better mechanical strength than glass fibre fabric
- Extremely durable & hard wearing hose
- Excellent flexibility
- Highly resistant to ozone
- Good vacuum resistance due to its specially designed structure
- Corrugated inner & outer appearance

#### APPLICATIONS

- Neoprene hose for the transference of air, fumes, dust & light solids
- Recommended for air, fume & particle extraction & suction, dust, exhaust gases & ventilation in general industries

#### CONSTRUCTION

- Double reinforced layers of chloroprene (neoprene) coated cotton with two spring steel helices
- Visible inner helix & second helix trapped between the layers of cloth

#### SPECIFICATIONS

Operational temperature range	-20°C to +100°C
Colour	Black inner & outer

#### USE PRECAUTIONS

The Wyrem hose is not pressure tight & should not be used in pressurised applications. In these cases, the maximum accepted pressure is 0.35 bar.

Gas & oil drops do not damage Wyrem, but the hose should not be used to transport fuel or oil & should never be submerged in these liquids.

PART NUMBER			
WY-800600000025	25	26.2	0.35
WY-800600000032	32	33.2	0.35
WY-800600000038	38	39.2	0.35
WY-800600000040	40	41.2	0.35
WY-800600000045	45	46.2	0.35
WY-800600000051	51	52.2	0.35
WY-800600000057	57	58.2	0.35
WY-800600000060	60	61.2	0.35
WY-800600000063	63	63.5	0.35
WY-800600000070	70	71.2	0.35
WY-800600000076	76	77.2	0.35
WY-800600000080	80	81.2	0.35
WY-800600000082	82	83.2	0.35
WY-800600000090	90	91.2	0.35
WY-800600000102	102	103.2	0.35
WY-800600000110	110	111.2	0.35
WY-800600000115	115	116.2	0.35
WY-800600000120	120	121.2	0.35
WY-800600000127	127	128.2	0.35
WY-800600000140	140	141.2	0.35
WY-800600000152	152	153.2	0.35
WY-800600000165	165	166.2	0.35
WY-800600000180	180	181.2	0.35
WY-800600000203	203	204.2	0.35
WY-800600000225	225	226.2	0.35
WY-800600000254	254	255.2	0.35
WY-800600000305	305	306.2	0.35

## PVC DUCTING

## LIGHTWEIGHT PVC DUCTING

#### SUITABILITY

- Suction & transport hose for solids, gaseous & liquid media
- Dust & fume extraction

#### FEATURES / BENEFITS

- Extremely flexible & lightweight
- Good resistance to oils, alkalis & acids
- Good chemical resistance
- Cable protection
- UV & ozone resistant

#### SPECIFICATIONS

Temperature range	-20°C to +70°C (intermittent to 80°C)
Construction	Soft PVC reinforced with high tensile PVC coated steel wire helix.

Supplied in full coils only

### MASTER PVC LFL 10 METRE COILS



1130

PART NUMBER				
MF-662L-025	25	1	13	1800
MF-662L-032	32	1 1/4	16	1800
MF-662L-038	38	1 1/2	20	1800
MF-662L-045	45	1 3/4	23	1400
MF-662L-051	51	2	26	1300
MF-662L-057	57	2 1/4	28	1200
MF-662L-063	63	2 1/2	31	1200
MF-662L-076	76	3	38	800
MF-662L-080	80	3 1/4	38	800
MF-662L-089	89	3 1/2	45	700
MF-662L-102	102	4	50	600
MF-662L-115	115	4 1/2	58	400
MF-662L-127	127	5	64	300
MF-662L-152	152	6	76	200