



FEATURES	BENEFITS
<ul style="list-style-type: none"> • Compact & lightweight • High flow capacity • Small external dimensions • Suitable for vacuum 	<ul style="list-style-type: none"> • Fast, easy, one hand operation • Extremely efficient
SPECIFICATIONS	
Nominal flow diameter	5 mm (3/16")
Flow capacity	580 l/min (20.5 CFM)*
Max. working pressure	35 bar (507 psi)
Min. burst pressure	140 bar (2,030 psi)
Temperature range	-30°C to +100°C (-22°F to +212°F)
Coupling material	Nickel plated brass
Nipple material	Hardened zinc plated steel

NPT threads are available




Not actual size



*Flow capacity measured at 6 bar (87 psi) inlet pressure & pressure drop at 0.5 bar (7 psi)

COUPLINGS



220 SERIES
HOSE BARB

210

PART NUMBER	TUBE ID	METRIC EQ.
C102201001	3/16"	5 mm
C102201002	1/4"	6 mm
C102201003	5/16"	8 mm
C102201004	3/8"	10 mm

NIPPLES



220 SERIES
HOSE BARB

210

PART NUMBER	TUBE ID	METRIC EQ.
C102205001	3/16"	5 mm
C102205002	1/4"	6 mm
C102205003	5/16"	8 mm
C102205004	3/8"	10 mm

220 SERIES
BSPT MALE



210

PART NUMBER	THREAD
C102201151	1/8" BSPT
C102201152	1/4" BSPT
C102201154	3/8" BSPT

220 SERIES
BSPT MALE



210

PART NUMBER	THREAD
C102205151	1/8" BSPT
C102205152	1/4" BSPT
C102205154	3/8" BSPT

220 SERIES
BSPP FEMALE



210

PART NUMBER	THREAD
C102201201	1/8" BSPP
C102201202	1/4" BSPP
C102201204	3/8" BSPP

220 SERIES
BSPP FEMALE



210

PART NUMBER	THREAD
C102205201	1/8" BSPP
C102205202	1/4" BSPP
C102205204	3/8" BSPP