

JUBILEE® HIGH TORQUE

FEATURES

Quality Assurance – Lloyd's Register Type Approval

SPECIFICATIONS

Material	304 stainless steel
Fastening	8 mm A/F screw
Corrosion resistance*	1000 hours NSS test



4110

New Additions

304 STAINLESS STEEL

PART NUMBER	CLAMPING RANGE	BAND WIDTH
J HT035	20 – 35 mm	16 mm
J HT040	25 – 40 mm	16 mm
J HT045	25 – 45 mm	16 mm
J HT050	30 – 50 mm	16 mm
J HT055	35 – 55 mm	16 mm
J HT060	40 – 60 mm	16 mm
J HT065	45 – 65 mm	16 mm
J HT070	40 – 70 mm	16 mm
J HT080	60 – 80 mm	16 mm
J HT095	70 – 95 mm	16 mm
J HT100	80 – 100 mm	16 mm
J HT120	90 – 120 mm	16 mm
J HT140	110 – 140 mm	16 mm
J HT160	130 – 160 mm	16 mm
J HT180	150 – 180 mm	16 mm
J HT200	170 – 200 mm	16 mm
J HT220	190 – 220 mm	16 mm
J HT240	210 – 240 mm	16 mm
J HT260	230 – 260 mm	16 mm
J HT280	250 – 280 mm	16 mm
J HT300	270 – 300 mm	16 mm
J HT320	290 – 320 mm	16 mm
J HT340	310 – 340 mm	16 mm
J HT360	330 – 360 mm	16 mm
J HT380	350 – 380 mm	16 mm
J HT400	370 – 400 mm	16 mm
J HT420	390 – 420 mm	16 mm
J HT440	410 – 440 mm	16 mm
J HT460	430 – 460 mm	16 mm
J HT480	450 – 480 mm	16 mm
J HT500	470 – 500 mm	16 mm
J HT520	490 – 520 mm	16 mm

FEATURES

Quality Assurance – Lloyd's Register Type Approval

SPECIFICATIONS

Material	316 stainless steel
Fastening	8 mm A/F screw
Corrosion resistance*	1000 hours NSS test



4110

New

316 STAINLESS STEEL

PART NUMBER	CLAMPING RANGE	BAND WIDTH
J HT035SS316	20 – 35mm	15.7 mm
J HT040SS316	25 – 40mm	15.7 mm
J HT045SS316	25 – 45mm	15.7 mm
J HT050SS316	30 – 50mm	15.7 mm
J HT055SS316	35 – 55mm	15.7 mm
J HT060SS316	40 – 60mm	15.7 mm
J HT065SS316	45 – 65mm	15.7 mm
J HT070SS316	40 – 70mm	15.7 mm
J HT080SS316	60 – 80mm	15.7 mm
J HT095SS316	70 – 95mm	15.7 mm
J HT100SS316	80 – 100mm	15.7 mm
J HT120SS316	90 – 120mm	15.7 mm
J HT140SS316	110 – 140mm	15.7 mm
J HT160SS316	130 – 160mm	15.7 mm
J HT180SS316	150 – 180mm	15.7 mm
J HT200SS316	170 – 200mm	15.7 mm
J HT220SS316	190 – 220mm	15.7 mm
J HT240SS316	210 – 240mm	15.7 mm
J HT260SS316	230 – 260mm	15.7 mm
J HT280SS316	250 – 280mm	15.7 mm
J HT300SS316	270 – 300mm	15.7 mm
J HT320SS316	290 – 320mm	15.7 mm
J HT340SS316	310 – 340mm	15.7 mm
J HT360SS316	330 – 360mm	15.7 mm
J HT380SS316	350 – 380mm	15.7 mm
J HT400SS316	370 – 400mm	15.7 mm
J HT420SS316	390 – 420mm	15.7 mm
J HT440SS316	410 – 440mm	15.7 mm
J HT460SS316	430 – 460mm	15.7 mm
J HT480SS316	450 – 480mm	15.7 mm
J HT500SS316	470 – 500mm	15.7 mm
J HT520SS316	490 – 520mm	15.7 mm

JUBILEE® WINGSPADE CLIP

FEATURES

Based on Jubilee® light range clips & suitable for hand fitting. Jubilee Wingspade clips are supplied with a thumb screw, allowing easy torquing using just a thumb & forefinger. Suited to fittings that may need to be removed from time to time, such as dust extraction units or domestic hoses.

SPECIFICATIONS

Material	Mild steel, zinc protected
Fastening	Wing screw
Corrosion resistance*	240 hours NSS test



4110

MILD STEEL CLIP

PART NUMBER	CLAMPING RANGE
J WS012	9.5 – 12 mm
J WS016	11 – 16 mm
J WS020	13 – 20 mm
J WS022	12 – 22 mm
J WS027	16 – 27 mm
J WS032	20 – 32 mm
J WS040	25 – 40 mm
J WS045	30 – 45 mm

* 240 hours is regarded by the British construction industry as the equivalent of a lifetime of 60 years in an urban outside environment in the UK