

JUBILEE® SUPERCLAMP

FEATURES

Quality Assurance – DIN 3017

SPECIFICATIONS

Material	Mild steel, zinc plated
Fastening	8 – 13 mm A/F bolt
Corrosion resistance*	168 hours NSS test



4110

FEATURES

Quality Assurance – DIN 3017

SPECIFICATIONS

Material	304 stainless steel
Fastening	8 – 13 mm A/F bolt
Corrosion resistance*	1000 hours NSS test



4110

MILD STEEL, ZINC PLATED

PART NUMBER	CLAMPING RANGE	BAND WIDTH
JSC019MS	17 – 19 mm	18 mm
JSC022MS	20 – 22 mm	18 mm
JSC025MS	23 – 25 mm	18 mm
JSC028MS	26 – 28 mm	18 mm
JSC031MS	29 – 31 mm	18 mm
JSC035MS	32 – 35 mm	20 mm
JSC039MS	36 – 39 mm	20 mm
JSC043MS	40 – 43 mm	20 mm
JSC047MS	44 – 47 mm	20 mm
JSC051MS	48 – 51 mm	20 mm
JSC055MS	52 – 55 mm	20 mm
JSC059MS	56 – 59 mm	20 mm
JSC063MS	60 – 63 mm	20 mm
JSC067MS	64 – 67 mm	25 mm
JSC073MS	68 – 73 mm	25 mm
JSC079MS	74 – 79 mm	25 mm
JSC085MS	80 – 85 mm	25 mm
JSC091MS	86 – 91 mm	25 mm
JSC097MS	92 – 97 mm	25 mm
JSC103MS	98 – 103 mm	25 mm
JSC112MS	104 – 112 mm	25 mm
JSC121MS	113 – 121 mm	25 mm
JSC130MS	122 – 130 mm	25 mm
JSC139MS	131 – 139 mm	25 mm
JSC148MS	140 – 148 mm	25 mm
JSC161MS	149 – 161 mm	25 mm
JSC174MS	162 – 174 mm	25 mm
JSC187MS	175 – 187 mm	25 mm
JSC200MS	188 – 200 mm	25 mm
JSC213MS	201 – 213 mm	25 mm
JSC226MS	214 – 226 mm	25 mm
JSC239MS	227 – 239 mm	25 mm
JSC255MS	240 – 255 mm	25 mm

304 STAINLESS STEEL

PART NUMBER	CLAMPING RANGE	BAND WIDTH
JSC019SS	17 – 19 mm	18 mm
JSC022SS	20 – 22 mm	18 mm
JSC025SS	23 – 25 mm	18 mm
JSC028SS	26 – 28 mm	18 mm
JSC031SS	29 – 31 mm	18 mm
JSC035SS	32 – 35 mm	20 mm
JSC039SS	36 – 39 mm	20 mm
JSC043SS	40 – 43 mm	20 mm
JSC047SS	44 – 47 mm	20 mm
JSC051SS	48 – 51 mm	20 mm
JSC055SS	52 – 55 mm	20 mm
JSC059SS	56 – 59 mm	20 mm
JSC063SS	60 – 63 mm	20 mm
JSC067SS	64 – 67 mm	25 mm
JSC073SS	68 – 73 mm	25 mm
JSC079SS	74 – 79 mm	25 mm
JSC085SS	80 – 85 mm	25 mm
JSC091SS	86 – 91 mm	25 mm
JSC097SS	92 – 97 mm	25 mm
JSC103SS	98 – 103 mm	25 mm
JSC112SS	104 – 112 mm	25 mm
JSC121SS	113 – 121 mm	25 mm
JSC130SS	122 – 130 mm	25 mm
JSC139SS	131 – 139 mm	25 mm
JSC148SS	140 – 148 mm	25 mm
JSC161SS	149 – 161 mm	25 mm
JSC174SS	162 – 174 mm	25 mm
JSC187SS	175 – 187 mm	25 mm
JSC200SS	188 – 200 mm	25 mm
JSC213SS	201 – 213 mm	25 mm
JSC226SS	214 – 226 mm	25 mm
JSC239SS	227 – 239 mm	25 mm
JSC255SS	240 – 255 mm	25 mm

* 240 hours is regarded by the British construction industry as the equivalent of a lifetime of 60 years in an urban outside environment in the UK

JUBILEE® DRIVERS

CLIPDRIVER 7 MM A/F SOCKET RIGID SHAFT



4110

PART NUMBER	DESCRIPTION
J CD95	95 mm hexagonal clip driver

FLEXDRIVER 7 MM A/F SOCKET FLEXIBLE SHAFT



4110

PART NUMBER	DESCRIPTION
J FLEXDRIVE	For use with Jubilee® clips