

## HOSE CLAMPS

### SPECIFICATIONS

|                       |                       |
|-----------------------|-----------------------|
| Max. working pressure | PN16 25 bar (363 psi) |
| Material              | Malleable iron        |

### FEATURES

- Robust clamps
- Easy & secure, for various fittings & applications

### TWO PART HOSE CLAMPS WITH LOOSE SADDLES & SAFETY CLAWS



906

### TWO PART HOSE CLAMPS WITH LOOSE SADDLES



906

| PART NUMBER | HOSE ID         | HOSE OD     |
|-------------|-----------------|-------------|
| SK 29       | 1/2" / 13 mm    | 22 – 29 mm  |
| SK 34       | 3/4" / 19 mm    | 28 – 32 mm  |
| SK 39       | 1" / 25 mm      | 35 – 42 mm  |
| SK 44       | 1 7/64" / 28 mm | 42 – 45 mm  |
| SK 51       | 1 3/8" / 35 mm  | 45 – 53 mm  |
| SK 60       | 1 5/8" / 42 mm  | 55 – 60 mm  |
| SK 73       | 2" / 50 mm      | 60 – 73 mm  |
| SK 75       | 3" / 75 mm      | 86 – 102 mm |

| PART NUMBER | HOSE ID        | HOSE OD      |
|-------------|----------------|--------------|
| SL 29*      | 1/2" / 13 mm   | 22 – 29 mm   |
| SL 34*      | 3/4" / 19 mm   | 28 – 34 mm   |
| SL 40*      | 1" / 25 mm     | 32 – 40 mm   |
| SL 49*      | 1 1/4" / 32 mm | 39 – 49 mm   |
| SL 60*      | 1 1/2" / 38 mm | 48 – 60 mm   |
| SL 72       | 2" / 50 mm     | 56 – 72 mm   |
| SL 76*      | 2" / 50 mm     | 60 – 76 mm   |
| SL 94*      | 2 1/2" / 63 mm | 77 – 94 mm   |
| SL 400      | 3" / 75 mm     | 89 – 101 mm  |
| SL 115      | 3" / 75 mm     | 94 – 115 mm  |
| SL 525      | 3 1/2" / 89 mm | 113 – 127 mm |
| SL 145      | 3 1/2" / 89 mm | 115 – 145 mm |
| SL 550      | 4" / 100 mm    | 127 – 140 mm |
| SL 600      | 4" / 100 mm    | 135 – 155 mm |
| SL 675      | 5" / 125 mm    | 155 – 175 mm |
| SL 769      | 6" / 150 mm    | 175 – 195 mm |
| SL 875      | 7" / 175 mm    | 210 – 225 mm |
| SL 988      | 8" / 200 mm    | 227 – 250 mm |

\*DIN 20039 A

## US HOSE CLAMPS

### FEATURES

- Robust clamps
- Easy & secure, for various fittings & applications

### SPECIFICATIONS

|                       |                                                                     |
|-----------------------|---------------------------------------------------------------------|
| Max. working pressure | 25 bar (363 psi)                                                    |
| Material              | Malleable iron, zinc plated & yellow passivated (free of chrome VI) |

### TWO PART US HOSE CLAMPS WITH SAFETY CLAWS



906

| PART NUMBER | HOSE ID      | HOSE OD    |
|-------------|--------------|------------|
| LB-4        | 1/2" / 13 mm | 21 – 27 mm |
| SKA 34      | 3/4" / 19 mm | 30 – 35 mm |
| LBU-9       | 3/4" / 19 mm | 30 – 33 mm |
| LB-9        | 3/4" / 19 mm | 33 – 38 mm |
| LB-10       | 3/4" / 19 mm | 38 – 43 mm |
| SKA 10      | 1" / 25 mm   | 35 – 45 mm |
| LBU-29      | 2" / 50 mm   | 63 – 70 mm |

## SUREFIX PIPE CLIPS

### SUREFIX RUBBER LINED GUIDE CLIP FEATURES

- Mild steel, BZP finish
- For use with copper & plastic tubes
- Silicone low friction lining

New

### RUBBER LINED GUIDE CLIP M8 / M10 BOSS NUT



4132

| PART NUMBER | TUBE OD |
|-------------|---------|
| GC16        | 16 mm   |
| GC20        | 20 mm   |
| GC25        | 25 mm   |
| GC32        | 32 mm   |
| GC40        | 40 mm   |
| GC50        | 50 mm   |
| GC56        | 56 mm   |
| GC63        | 63 mm   |