

620

620

# **CEJN Blow Guns –** Series 208

### 208 Blow Gun Features

- Suspension possible by both the built-in hook and the handle
  The normal grip is adjusted to fit the hand during normal usage
- Infinitely variable airflow with high volume flow for efficient cleaning

### 208 Detect Blow Gun Additional Features

### SPECIFICATIONS

Airflow at inlet pressure of 6 bar (87 psi) 500 l/m (18 CFM)

Max. working pressure

Standard blow guns: 16 bar (232 psi) 8 bar (116 psi) blow gun with regulator

Temperature range -20°C to +60°C (-4°F to +140°F)



## APPLICABLE SAFETY STANDARDS



The products with the 'OK' symbol are compliant with the OSHA directive STD1-13.1 (1910-242(b)). When dead ending occurs, static pressure at the main orifice shall not exceed 30 psi (2 bar).



The products with the 'ear' symbol are compliant with the International Standard ISO 4414 - Pneumatic Fluid Power & OSHA 1910.95 - Occupational Noise Exposure. These products have a sound level below 85 dBA & meet the EU Machine Directive §1.5.8. concerning noise reduction demands.

# **BLOW GUNS - SERIES 208**



## **BLOW GUN WITHOUT NOZZLE**

1/4" BSPT

DESCRIPTION

PART NUMBER C112080000

Blow gun, no nozzle supplied



**BLOW GUN WITH REGULATOR** 

1/4" BSPT

DESCRIPTION C112080300

PART NUMBER

Blow gun 90 mm, automatic shut-off



## **BLOW GUN WITH 90 MM TUBE**

DETECT BLOW GUN - SERIES 208

1/4" BSPT

PART NUMBER DESCRIPTION C112080100 Blow gun, non-removable nozzle C112080200 Blow gun, removable nozzle



620

## **BLOW GUN WITH STAR-TIP** 1/4" BSPT

PART NUMBER

C112083100 C112083200

DESCRIPTION Blow gun 90 mm, non-removable nozzle Blow gun 90 mm, removable nozzle

# **BLOW GUN DISPLAY CASE**





DETECT BLOW GUN

1/4" BSPT

PART NUMBER C112089990

DESCRIPTION Blow gun, non-removable nozzle





PART NUMBER C112089984

DESCRIPTION 20 x C112080100

