

## REELWORKS SERIES

### POLYPROPYLENE 60°C MAX

#### FEATURES / BENEFITS

- Lightweight & durable, just 5.7 kg
- Constructed in high-impact UV stabilised polypropylene
- Supplied with fitted PVC hose for immediate installation
- Fully assembled, includes 3 ft connecting hose
- Suitable for compressed air & water
- Integral wall / overhead mounting bracket
- Latching of hose at any length
- Fully automatic hose rewind for neat & tidy storage
- Virtually maintenance free



PART NUMBER	HOSE ID	LENGTH	INLET / OUTLET
hC705100	1/4"	10 m	1/4"
hC705200	5/16"	8 m	1/4"

### POLYMER HOSE COMPACT

#### FEATURES / BENEFITS

- Supplied with 15 m x 3/8" or 1/2" flexible, premium hybrid polymer hose
- Hose has no memory & lays flat when in use
- High quality, durable polypropylene housing
- Fully automatic spring rewind
- Low effort, easy to use, rewind tension
- Integral pivoting wall bracket, swivels through 180°
- Latching of hose at any length
- Latching system can be set to free run if required
- Working pressure up to 300 psi (20 bar)



PART NUMBER	HOSE ID	LENGTH	INLET / OUTLET
hC2752	3/8"	15 m	3/8"
hC2753	1/2"	15 m	1/2"

### POLYMER HIGH VISIBILITY HOSE

#### FEATURES / BENEFITS

- Automatic guide system – no bunching of hose, layers hose from side to side, neat & tidy every time
- Slow retraction system – prevents hose from speeding back to the reel if the hose is let go – safe operation
- Low tension spring
- Latching of hose at any length



PART NUMBER	HOSE CAPACITY	HOSE ID	INLET / OUTLET
hC2782	15 m	3/8"	3/8"
hC2783	15 m	1/2"	1/2"

### POLYPROPYLENE GARDEN HOSE

#### FEATURES / BENEFITS

- Lightweight & durable, just 10.6 kg
- Constructed in high impact UV stabilised polypropylene
- Supplied & fitted with PVC hose for immediate & trouble free installation
- Fully assembled, includes 36" / 0.9 m connecting hose
- Complete with water gun & convenient handle for portable use
- Fitted with speed, control to help automatic hose rewinding constant & at a safe speed keeping it under control at all times
- Hose layering system ensures neat & trouble free storage of hose
- Spring fully enclosed & lubricated
- Integral wall / overhead pivoting bracket
- Non-sag rollers reduce hose wear



PART NUMBER	HOSE CAPACITY	HOSE ID	MAX. WORKING PRESSURE
hC2766	20 m	1/2"	10 bar