

FLEX TYPE A FEATURES

- High impact resistant composite housing
- 7 models selected for a load range from 0 to 3.5 kg
- Adjustable spring load throughout & ergonomic handgrip knob
- Adjustable rope stroke
- Available with nylon braided rope or steel braided, nylon coated wire
- Tools in conformity with CE directives



4610

FLEX TYPE B FEATURES

- Metal housing
- 14 models selected for a load range from 0.5 to 11 kg
- Adjustable spring load throughout & safety removable handle
- Adjustable rope stroke
- Available with nylon braided rope or steel braided, nylon coated wire
- Tools in conformity with CE directives



4610

FLEX TYPE A NYLON BRAIDED ROPE

PART NUMBER	LOADING CAPACITY	WEIGHT	CORD LENGTH
SF0-05	0 – 0.5 kg	0.3 kg	2.3 m
SF05-1	0.5 – 1 kg	0.35 kg	2.3 m
SF1-2	1 – 2 kg	0.4 kg	2.3 m
SF2-35	2 – 3.5 kg	0.4 kg	2.3 m

FLEX TYPE B NYLON ROPE

PART NUMBER	LOADING CAPACITY	WEIGHT	CORD LENGTH
FLEX05-1	0.5 – 1 kg	0.6 kg	2.3 m
FLEX05-15	0.5 – 1.5 kg	0.6 kg	2.3 m
FLEX1-2	1 – 2 kg	0.65 kg	2.3 m
FLEX2-35	2 – 3.5 kg	0.65 kg	2.3 m

STEEL BRAIDED NYLON COATED WIRE

FLEX05-1A	0.5 – 1 kg	0.6 kg	2.3 m
FLEX05-15A	0.5 - 1.5 kg	0.6 kg	2.3 m
FLEX1-2A	1 - 2 kg	0.65 kg	2.3 m
FLEX2-35A	2 - 3.5 kg	0.65 kg	2.3 m
FLEX3-6A	3 - 6 kg	1.64 kg	2.3 m
FLEX5-85A	5 - 8.5 kg	1.7 kg	2.3 m
FLEX8-11A	8 - 11 kg	1.75 kg	2.3 m

FLEX TYPE C FEATURES

- Metal housing
- 10 models selected for a load range from 1 to 70 kg
- Adjustable spring load
- Adjustable rope stroke
- Steel rope
- Safety device against spring break off
- Tools in conformity with CE directives



4610

MATIC FEATURES

- Composite housing
- 3 models selected for a load range from 0.5 to 5 kg
- Adjustable spring load
- 6.5 x 10 mm soft braided polyurethane hose
- Adjustable hose stroke
- Tools in conformity with CE directives



4610

FLEX TYPE C

PART NUMBER	LOADING CAPACITY	WEIGHT	CORD LENGTH
FLEX-3	1 – 3 kg	1.4 kg	1.5 m
FLEX-5	3 – 5 kg	1.5 kg	1.5 m
FLEX-9	5 – 9 kg	3.4 kg	1.5 m
FLEX-15	9 – 15 kg	3.8 kg	1.5 m
FLEX-22	15 – 22 kg	7.2 kg	1.5 m
FLEX-30	22 – 30 kg	8.5 kg	1.5 m
FLEX-40	30 – 40 kg	9.8 kg	1.5 m
FLEX-50	40 – 50 kg	10.4 kg	1.5 m
FLEX-60	50 – 60 kg	11.6 kg	1.5 m
FLEX-70	60 – 70 kg	11.8 kg	1.5 m

MATIC

PART NUMBER	LOADING CAPACITY	WEIGHT	CORD LENGTH
MATIC15	0.5 – 1.5 kg	1.6 kg	1.6 m
MATIC30	1.5 – 3.0 kg	1.7 kg	1.6 m
MATIC50	3.0 – 5.0 kg	1.8 kg	1.6 m

Matic hose diameter internal: 6.5 mm, external: 10 mm
Maximum working pressure: 10 bar