

STANDARD FITTINGS - Look for this symbol

- Grip & seal cartridge with stainless steel teeth & main O-ring seal
- Compatible with hot & cold water & central heating systems, unless stated otherwise
- Suitable for use with plastic or copper pipe





T

В

AP CONNECTOR SPP FEMALE	र		2140
PART NUMBER	TUBE OD	THREAD	
FART NOWIDER	TOBE OD	HINLAD	
JGPSE3210W	10 mm	1/2" BSPP	

PART NUMBER	TUBE OD	THREAD
JGPSE3210W	10 mm	1/2" BSPP
JGPSE3201W	15 mm	1/2" BSPP
JGPSE3203W	15 mm	3/4" BSPP
JGPSE3202W	22 mm	3/4" BSPP

Requires hand tightening only Note: Plastic threads are not as strong as metal threads



STOP FND

PART NUMBER

JGPSE4610W

JGPSE4615W JGPSE4622W



		2170
1	TUBE OD	
	10 mm	
	15 mm	

Safely & easily caps off pipework for a temporary or permanent installation. Suitable for central heating systems

22 mm



PIPE INSERT

FOR COMPRESSION FITTINGS

PART NUMBER	TUBE OD	
JGTSM10N	10 mm	
JGSTM15N	15 mm	
JGSTM22N	22 mm	
JGSTM28N	28 mm	

To be used when connecting Speedfit pipe to a compression fitting or fitting from another manufacturer. Suitable for hot & cold water & central heating systems



TANK CONNECTOR



PART NUMBER	TUBE OD	
JGCM0715S	15 mm	
JGCM0722S	22 mm	
JGCM0728S	28 mm	

Suitable for cold water tanks only

Maximum wall thickness of tank 4 mm. Requires hand tightening only

PIPE INSERT



SUPERSEAL

PART NUMBER	TUBE OD	
JGSTS10	10 mm	
JGSTS15	15 mm	
JGSTS22	22 mm	
JGSTS28	28 mm	

Only to be used with Speedfit pipe & Speedfit fittings together, to give enhanced sealing. Creates a rigid connection & enhanced double seal when fitting a Speedfit pipe to a Speedfit fitting. Suitable for hot & cold water & central heating systems







2140

2140

PART NUMBER	TUBE OD	
JGPL10	10 mm	
JGPL15	15 mm	
JGPL22	22 mm	
JGPL28	28 mm	

Safely plug a connection port on a Speedfit fitting, when not required. Suitable for central heating systems



PE-COPPER CONNECTOR

PART NUMBER	TUBE OD	TUBE OD
JGJG601B	20 mm	15 mm
JGJG603B	25 mm	15 mm
JGJG602B	25 mm	22 mm

Used to connect PE pipe to copper or Speedfit plumbing pipe. Must not be buried directly into ground, soil, concrete or other substrates. Safely & securely connects MDPE to copper or Speedfit pipe (inserts required)

ACETAL FITTINGS FOR DRINKS & OTHER POTABLE WATER

ACETAL FITTINGS

CM range of metric size fittings are manufactured in acetal. With a food grade EPDM O-ring, they have been developed for the water industry but are equally suitable for other potable liquids. They are also recommended for intermittent hot water applications. The CM Range is NOT suitable for compressed air & vacuum applications.



ADAPTOR **BSPP MALE**



PART NUMBER	TUBE OD	THREAD	
JGCM011514S	15 mm	1/2" BSPP	
JGCM012216S	22 mm	3/4" BSPP	





RT NUMBER	TUBE OD	THREAD
CM321014E	10 mm	1/2" BSPP