


STANDARD FITTINGS - Look for this symbol



- Compatible with hot & cold water & central heating systems, unless stated otherwise
- · Suitable for use with plastic or copper pipe





TAP CONNECTOR **BSPP FEMALE**

PART NUMBER	TUBE OD	THREAD
JGPSE3210W	10 mm	1/2" BSPP
JGPSE3201W	15 mm	1/2" BSPP
JGPSE3203W	15 mm	3/4" BSPP
JGPSF3202W	22 mm	3/4" BSPP

Requires hand tightening only

Note: Plastic threads are not as strong as metal threads





STOP END

PART NUMBER	TUBE OD	
JGPSE4610W	10 mm	
JGPSE4615W	15 mm	
JGPSE4622W	22 mm	

Safely & easily caps off pipework for a temporary or permanent installation. Suitable for central heating systems



PIPE INSERT

FOR COMPRESSION FITTINGS

PART NUMBER	TUBE OD	
JGTSM10N	10 mm	
JGSTM15N	15 mm	
JGSTM22N	22 mm	
JGSTM28N	28 mm	

To be used when connecting Speedfit pipe to a compression fitting or fitting from another manufacturer. Suitable for hot & cold water & central heating systems





TANK CONNECTOR

PART NUMBER	TUBE OD	
JGCM0715S	15 mm	
JGCM0722S	22 mm	
JGCM0728S	28 mm	

Suitable for cold water tanks only

Maximum wall thickness of tank 4 mm. Requires hand tightening only

PIPE INSERT

SUPERSEAL



PART NUMBER TURE OF JGSTS10 10 mm JGSTS15 15 mm JGSTS22 22 mm JGSTS28 28 mm

Only to be used with Speedfit pipe & Speedfit fittings together, to give enhanced sealing. Creates a rigid connection & enhanced double seal when fitting a Speedfit pipe to a Speedfit fitting

Suitable for hot & cold water & central heating systems



2140



2140

2140

PART NUMBER	TUBE OD
JGPL10	10 mm
JGPL15	15 mm
JGPL22	22 mm
JGPL28	28 mm

Safely plug a connection port on a Speedfit fitting, when not required. Suitable for central heating systems



PE-COPPER CONNECTOR

PART NUMBER	TUBE OD	TUBE OD
JGJG601B	20 mm	15 mm
JGJG603B	25 mm	15 mm
JGJG602B	25 mm	22 mm

Used to connect PE pipe to copper or Speedfit plumbing pipe. Must not be buried directly into ground, soil, concrete or other substrates. Safely & securely connects MDPE to copper or Speedfit pipe (inserts required).

ACETAL FITTINGS FOR DRINKS & OTHER POTABLE WATER

ACETAL FITTINGS

CM range of metric size fittings are manufactured in acetal. With a food grade EPDM O-ring, they have been developed for the water industry but are equally suitable for other potable liquids. They are also recommended for intermittent hot water applications. The CM Range is NOT suitable for compressed air & vacuum applications.



ADAPTOR





PART NUMBER	TUBE OD	THREAD
JGCM011514S	15 mm	1/2" BSPP
JGCM012216S	22 mm	3/4" BSPP





PART NUMBER	TUBE OD	THREAD
JGCM321014E	10 mm	1/2" BSPP