

VACUUM SWITCHES

SPECIFICATIONS

Thread	1/4" BSPT
Max. switched voltage	48 V
Setting range	-200 / -900 m bar
Tolerance at 20°C	± 100
Max. switched current	0.5 A
Max. fluid temperature	80°C to 120°C
Action type	1B
Max. overpressure limit	15 bar
Max. working pressure	10 bar

MATERIALS

Case	Brass
Electrical contacts	Silver AgNi



5940

VACUUM SWITCH

PART NUMBER	DESCRIPTION
SPVL3511219	Normally open
SPVL3521219	Normally closed

SPECIFICATIONS

Thread	1/4" BSPT
Voltage	240 V
Max. fluid temperature	80°C to 120°C depending on diaphragm
Action type	1B
Protection degree	IP65
Max. tightening torque	25 Nm
Max. overpressure limit	15 bar
Max. working pressure	10 bar

MATERIALS

Case	Brass
Electrical contacts	Silver



5940

DIAPHRAGM VACUUM SWITCH WITH SPDT CONTACTS NORMALLY OPEN

PART NUMBER	SETTING RANGE	TOLERANCE AT 20°C
SPVL3821229	-200 / -900 m bar	± 100 m bar

LEVEL SWITCHES

SPECIFICATIONS

Temperature range (atm. pressure)	-10°C to +80°C
Pressure resistance (room temperature)	0.2 MPa
Specific gravity of the liquid	Heavier than 0.8

MATERIALS

Stem	PP
Float	PP foamed
Stopper	SUS304 (PP)
Nat	PP

ELECTRIC SPECIFICATIONS

Max. contact capacity	50 W DC / AC
Max. voltage	300 V DC / AC
Max. current	0.5 A DC / AC



5940

SIDE ENTRY LEVEL SWITCH EXTERNAL FITTING

PART NUMBER	THREAD
SPVLMFS10N1	1/2" BSPT



5940

POLYPROPYLENE TOP ENTRY LEVEL SWITCH WITH 25 MM FLOAT

PART NUMBER	THREAD
SPVLMFS17C	1/8" BSPP

FLOAT VALVES

FEATURES

- Connection with gas thread cylindrical DIN – ISO 228/1985
- Guarantees a perfect seal with minimum force from the float
- Maximum variable pressure 10 bar
- Nominal pressure PN-10
- Patented valve system
- Swing type valve
- Valve closes progressively



5940

FLOAT VALVE 304 STAINLESS STEEL

PART NUMBER	THREAD
SPVL11-00110-B1	3/8"
SPVL11-00115-B1	1/2"
SPVL11-00120-B1	3/4"
SPVL11-00125-B1	1"
SPVL11-00132-B1	1 1/4"