

## FEATURES / BENEFITS

- Includes Certificate of Calibration
- Multiscale analogue bar gauge
- Accuracy exceeds EC Standards
- Tough die cast aluminium housing
- Wire sheathed hose eliminates kinking
- Impact absorbing bumpers
- Comfortable rubber grip on chuck handle

## SPECIFICATIONS

Reading accuracy	± 0.1 bar @ 1.7 – 5 bar (± 2 psi @ 25 – 75 psi)
Max. inflation pressure	9.6 bar (138 psi)
Max. inlet pressure	13.8 bar (200 psi)
Inflation speed / flow rate	500 l/min @ 13 bar (188 psi)



New

## TDR2000 TYRE INFLATOR

6130

PART NUMBER	HOSE LENGTH	VALVE CONNECTION
TI-102000	0.5 m (21")	Twin hold-on
TI-1020004	1.8 m (6 ft)	Single clip-on
TI-1020005	1.8 m (6 ft)	Twin clip-on

## FEATURES / BENEFITS

- Includes Certificate of Calibration
- Multiscale gauge
- Large backlit digital display
- Accuracy exceeds EC Standards
- Auto ON upon pressure sensing
- Auto OFF after 9 seconds
- Tough die cast aluminium housing
- Wire sheathed hose eliminates kinking
- Impact absorbing bumpers
- Comfortable rubber grip on chuck handle

## SPECIFICATIONS

Reading accuracy	± 0.1 bar @ 1.7 – 5 bar (± 2 psi @ 25 – 75 psi)
Max. inflation pressure	12 bar (174 psi)
Max. inlet pressure	13.8 bar (200 psi)
Inflation speed / flow rate	500 l/min @ 13 bar (188 psi)



New

## TDR3000 TYRE INFLATOR DIGITAL

6130

PART NUMBER	HOSE LENGTH	VALVE CONNECTION
TI-103012	0.5 m (21")	Hold-on
TI-1030123	1.8 m (6 ft)	Clip-on
TI-1030122	2.7 m (9 ft)	Clip-on

## FEATURES / BENEFITS

- Includes Certificate of Calibration
- Multiscale gauge
- Large tilted LCD backlit display
- Accuracy exceeds EC Standards
- Auto ON upon pressure sensing
- Auto OFF after 90 seconds
- Tough, lightweight diecast aluminium internal body with composite outer casing
- Wire sheathed hose eliminates kinking
- Impact absorbing bumpers
- Lightweight & robust

## SPECIFICATIONS

Reading accuracy	± 0.1 bar @ 1.7 – 5 bar (± 2 psi @ 25 – 75 psi)
Max. inflation pressure	12 bar (174 psi)
Max. inlet pressure	13.8 bar (200 psi)
Inflation speed / flow rate	1200 l/min @ 13.8 bar (200 psi)



New

## TDR4000 TYRE INFLATOR DIGITAL

6130

PART NUMBER	HOSE LENGTH	VALVE CONNECTION
TI-110723	0.5 m (21")	Clip-on
TI-1107232	1.8 m (6 ft)	Clip-on

## FEATURES / BENEFITS

- Includes Certificate of Calibration
- Multiscale gauge
- Accuracy exceeds EC Standards
- Tough, lightweight diecast aluminium internal body with composite outer casing
- Wire sheathed hose eliminates kinking
- Impact absorbing bumper
- Large 80 mm dial gauge
- IP rated

## SPECIFICATIONS

Reading accuracy	± 0.1 bar @ 1.7 – 5 bar (± 2 psi @ 25 – 75 psi)
Max. inflation pressure	12 bar (174 psi)
Max. inlet pressure	13.8 bar (200 psi)
Inflation speed / flow rate	1200 l/min @ 13.8 bar (200 psi)



New

## TDR5000 TYRE INFLATOR DIAL GAUGE

6130

PART NUMBER	HOSE LENGTH	VALVE CONNECTION
TI-110734	0.5 m (21")	Clip-on
TI-1107342	1.8 m (6 ft)	Clip-on