

FEATURES / BENEFITS

- Rechargeable lithium ion battery
- Fully rechargeable through a USB connection
- Ceramic sensor
- Integrated ergonomic inflate / deflate trigger
- Interchangeable 3 pressure ranges psi, bar, kPa
- 0.5 to 12 bar (7 to 174 psi) inflation range
- Accuracy exceeds EC86/217 & BSEN 12645:2014
- Auto OFF after 90 seconds of inactivity
- 1.8 m hose with single clip-on connector

SPECIFICATIONS

Reading accuracy	± 0.1 bar @ 1.7 – 5 bar (± 2 psi @ 25 – 75 psi)
Max. inflation pressure	12 bar (174 psi)
Max. inlet pressure	13.8 bar (200 psi)
Inflation speed / flow rate	500 l/min @ 13 bar (188 psi)



6130



**DIGITEC TYRE INFLATOR
RECHARGEABLE**

PART NUMBER	HOSE LENGTH	VALVE CONNECTION
TI-112015	1.8 m (6 ft)	Clip-on



**TWIN VALVE CONNECTOR
HOLD ON**



6130

PART NUMBER	DESCRIPTION	THREAD
TI-030465	Open end connector	1/4" BSPP
TI-030472	Closed end connector	1/4" BSPP



**TWIN VALVE CONNECTOR
CLIP ON**



6130

PART NUMBER	DESCRIPTION	THREAD
TI-030435	Open end connector	1/4" BSPP
TI-030435NS	Closed end connector	1/4" BSPP



CLIP ON CHUCK



6130

PART NUMBER	THREAD
TI-030447	1/4" BSPP

Do you also need?



Hose reels



Find it on pages 743 – 744, section twelve