

| FEATURES | BENEFITS |
|---|--|
| <ul style="list-style-type: none"> • Two line connection • Separate flow paths • CPC thumb latch • Free coupling rotation | <ul style="list-style-type: none"> • Fast, efficient operation • Pressure and / or vacuum in one coupling • One hand connection & disconnection • Eliminates kinked tubing |
| SPECIFICATIONS | |
| Bodies & inserts | Acetal or ABS |
| Springs, pin, latch | Stainless steel |
| Seal material | NBR |
| Working pressure | Vacuum to 120 psi (8.3 bar) per line |
| Operating temperature | -40°C to +82°C (-40°F to +180°F) |



COUPLING BODIES

COUPLING INSERTS

PANEL MOUNT – UNVALVED HOSE BARB – ACETAL



800

| PART NUMBER | TUBE ID | METRIC EQ. |
|-------------|---------|------------|
| cPTC 160-10 | 1/16" | 1.6 mm |
| cPTC 160-20 | 1/8" | 3.2 mm |

IN-LINE – UNVALVED HOSE BARB – ACETAL



800

| PART NUMBER | TUBE ID | METRIC EQ. |
|-------------|---------|------------|
| cPTC 220-10 | 1/16" | 1.6 mm |
| cPTC 220-20 | 1/8" | 3.2 mm |

PANEL MOUNT – UNVALVED HOSE BARB – ABS



800

| PART NUMBER | TUBE ID | METRIC EQ. |
|-------------|---------|------------|
| cPTC1602096 | 1/8" | 3.2 mm |

IN-LINE – UNVALVED HOSE BARB – ABS



800

| PART NUMBER | TUBE ID | METRIC EQ. |
|-------------|---------|------------|
| cPTC2202096 | 1/8" | 3.2 mm |

Do you also need?



DTLD & DPC series connectors



Find it on page 96, section two