



FEATURES

- · Suitable for use with oils up to 120 SAE
- Suitable for use with engine oil, synthetic oil, hydraulic oil, gear oil & automatic transmission fluid
- Low noise level quiet, efficient & reliable
- Supplied with 2" bung adaptor
- · 2 years manufacturer's warranty

SPECIFICATIONS

Ratio	1:1
Working pressure	5 - 8 bar (70 - 115 psi)
Air consumption	100 l/min
Output capacity	18 l/min
Suction tube diameter	42 mm
Air inlet connection	1/4" quick plug
Oil delivery connection	1/2" male
Max. viscosity	120 SAE



1:1 OIL PUMP SYSTEM

PART NUMBER	DESCRIPTION	
GR-J100TDG	Manual gun	
GR-J100TDGD	Digital gun	

FEATURES

Mobile pneumatic oil dispenser, designed for filling & topping up reservoirs. Pneumatic oil dispenser is equipped with a level gauge, delivery gun & flexible end.

- Works autonomously without the requirement of continuous connection to air supply
- Suitable for dispensing automotive engine & gearbox oils

SPECIFICATIONS

Air pressure	7 – 8 bar / 100 – 114 psi
Maximum pressure	10 bar / 145 psi
Flex hose	2000 mm / 79"



MOBILE PNEUMATIC OIL DISPENSER

PART NUMBER	CAPACITY	WEIGHT
GR-JPOD030	30 litre	15 kg
GR-JPOD065	65 litre	26 kg

FEATURES

- Unique front action operation allows the pump to be used on barrels placed in corners & other inaccessible areas
- Heavy duty aluminium die cast pump head incorporates 2" bung threads
- Brass piston rings for increased life
- Built-in nozzle holder for convenient storage of discharge hose
- Includes 1.8 m PVC NBR delivery hose with metal nozzle, spring & hose clamp
- Supplied complete with telescopic suction tube for use on 50 litre (15 gallons) 205 litre (55 gallons) drums
- Wetted components: steel, aluminium, brass, NBR & PVC NBR
- Recommended use: for dispensing diesel, kerosene, heating oils, motor oils, lubricating oils (up to SAE 90) & other non-corrosive media
- Do not use with water based media, antifreeze, solvents, acids & gasoline, etc.



HAND OPERATED BARREL PUMP

PART NUMBER	DESCRIPTION	
GR-ZA2HBL	Barrel pump	

DESCRIPTION

The J1703001 self priming lever pump is manufactured in steel, which is zinc plated to give a quality finish. Supplied with self adjusting, telescopic suction tube & 2" bung nut.

FEATURES

- Cushioned vinyl handle
- Supplied with self-adjusting suction tube
- Dispenses approximately 300 cc per stroke
- Zinc plated for lasting quality & appearance
 Suitable for use with 50 205 litre drums



LEVER HAND PUMP

PART NUMBER	DESCRIPTION	
GR-J1703001	Suitable for 50 - 205 litre drums	

DESCRIPTION

The J1703004 rotary action vane type pump is suitable for dispensing diesel & lubricating oils, up to SAE 90, output of up to 25 l/min.

FEATURES

- Supplied with 3 piece suction tube & 2" bung adaptor
- Built-in suction strainer
- Suitable for dispensing diesel & lubricating oils up to SAE 90
- Output up to 25 l/min
- Suitable for use with 50 205 litre drums



ROTARY BARREL PUMP

PART NUMBER	DESCRIPTION
GR-J1703004	Suitable for 50 – 205 litre drums