

SPECIFICATIONS	P CW254TC	P CW504TCAL	P CW5010AL	P CW5015AL	P CW5024AL	P CW50224AL
Working pressure	8 bar	8 bar	8 bar	8 bar	8 bar	8 bar
Noise level	40 dBA	45 dBA	45 dBA	45 dBA	45 dBA	47 dBA
Voltage	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Dimensions L x D x H	340 x 350 x 340 mm	340 x 350 x 340 mm	330 x 350 x 450 mm	350 x 350 x 480 mm	400 x 400 x 510 mm	400 x 400 x 510 mm



3.5 LITRE TANK
0.25 HP / 0.20 KW

1210

PART NUMBER	INPUT	OUTPUT @ 5 BAR	WEIGHT
P CW254TC	25 l/min	18.5 l/min	16 kg



3.5 LITRE TANK
0.50 HP / 0.35 KW

1210

PART NUMBER	INPUT	OUTPUT @ 5 BAR	WEIGHT
P CW504TCAL	50 l/min	37 l/min	22 kg



10 LITRE TANK
0.50 HP / 0.35 KW

1210

PART NUMBER	INPUT	OUTPUT @ 5 BAR	WEIGHT
P CW5010AL	50 l/min	37 l/min	23 kg



15 LITRE TANK
0.50 HP / 0.35 KW

1210

PART NUMBER	INPUT	OUTPUT @ 5 BAR	WEIGHT
P CW5015AL	50 l/min	37 l/min	28 kg



24 LITRE TANK
0.50 HP / 0.35 KW

1210

PART NUMBER	INPUT	OUTPUT @ 5 BAR	WEIGHT
P CW5024AL	50 l/min	37 l/min	30 kg



24 LITRE TANK
1.00 HP / 0.70 KW

1210

PART NUMBER	INPUT	OUTPUT @ 5 BAR	WEIGHT
P CW50224AL	100 l/min	74 l/min	44 kg

INTERIM SERVICE KITS

OIL, AIR FILTER, SEALS & GASKETS

1240

PART NUMBER	SERIES
P CW25ISK	CW25
P CW50ISK	CW50
P CW50X2ISK	CW50x2

MAIN SERVICE KITS

OIL, AIR FILTER, SEALS, GASKETS & VALVE PLATE KIT

1240

PART NUMBER	SERIES
P CW25MSK	CW25
P CW50MSK	CW50
P CW50X2MSK	CW50x2

