

## PIPE & THREAD SEALING

### 55 SERIES

- Fittings can be backed off up to 45° for alignment without fear of leakage
  - WRAS approval for drinking water & approved for use on gas fittings
- |                           |                                       |
|---------------------------|---------------------------------------|
| Maximum thread size       | Tested to 4"                          |
| Temperature resistance    | 130°C                                 |
| Substrate to be sealed    | Metal, plastic or both                |
| Instant low pressure seal | Yes (full pressure) on taper fittings |



3000

### 55 SERIES 50 M

PART NUMBER	SIZE	STRENGTH
LT55-50	50 m	Low

## THREADLOCKING

### 243 SERIES – GENERAL PURPOSE

Maximum thread size	M36
Temperature resistance	180°C
Substrate to be sealed	Metal



3000

### 243 SERIES THREADLOCKER

PART NUMBER	SIZE	STRENGTH
LT243-10	10 ml	Medium
LT243-50	50 ml	Medium

New

### 542 SERIES – HYDRAULIC & PNEUMATIC

Maximum thread size	3/4"
Temperature resistance	150°C
Substrate to be sealed	Metal
Instant low pressure seal	No



3000

### 542 SERIES HYDRAULIC & PNEUMATIC 50 ML

PART NUMBER	SIZE	STRENGTH
LT542-5	50 ml	Medium

### 270 SERIES – GENERAL PURPOSE

Temperature resistance	180°C
Substrate to be sealed	Metal



3000

### 270 SERIES THREADLOCKER

PART NUMBER	SIZE	STRENGTH
LT270-10	10 ml	High
LT270-50	50 ml	High

New

### 577 SERIES – GENERAL PURPOSE

Maximum thread size	3"
Temperature resistance	180°C
Substrate to be sealed	Metal
Instant low pressure seal	Yes on taper / parallel fittings



3000

### 577 SERIES GENERAL PURPOSE

PART NUMBER	SIZE	STRENGTH
LT577-5	50 ml	Medium
LT577-250	250 ml	Medium

### 648 SERIES – GENERAL PURPOSE

Temperature resistance	180°C
Substrate to be sealed	Metal



3000

### 648 SERIES RETAINING COMPOUND 50 ML

PART NUMBER	SIZE	STRENGTH
LT648-50	50 ml	High

New