

PARKAIR[®]

LUBRICATING OIL

VG 22 AIRLINE OIL is a premier quality airline oil of naturally high viscosity index, intended for the lubrication of pneumatic tools, valves & associated equipment. The product is intended for use in systems where it may be necessary to draw off any separated water. VG 22 AIRLINE OIL is inhibited to minimise thermal degradation & foaming, & protect against corrosion & deposit formation. The product is formulated to ensure rapid formation of a mist for lubrication of downstream pneumatic equipment.



LUBRICATING OIL GRADE 22 HM TYPE

PART NUMBER	DESCRIPTION	
H01LL	1 litre	
H05LL	5 litre	
H20LL	20 litre	

HYDRAULIC OIL

Premium quality hydraulic oil with additives to improve ageing resistance, corrosion & wear protection, demulsifying.

PERFORMANCE / SPECIFICATIONS

HLP hydraulic oil according to DIN 51524-2, ISO 11158-HM.



BOSS LEAK DETECTOR

BOSSTM Gas Leak Detector spray is a micro-porous foam that will show the smallest gas leaks as bubbles. Spray as upright as possible over joints / connections. It uses a non-flammable CO₂ propellant that does not react with other gases.



9110

BOSS LEAK DETECTOR

PART	NUMBER	
Q84636019		

DESCRIPTION 400 ml

COMPRESSOR OIL

Sincom/32E is a high performance synthetic compressor oil with antioxidant & antifoam additives. Tailored for high temperature air compressor operation, up to 220°C.



1240

COMPRESSOR OIL SYNTHETIC OIL & FILLER NOZZLE

PART NUMBER	DESCRIPTION
P C1069	0.5 litre bottle

P-80 FEATURES

P-80 emulsion is a unique assembly aid, formulated to provide temporary lubrication, making inserts easy to install, remove, or manipulate. For use in manufacturing operations involving natural or synthetic rubber or plastics. Water based, biodegradable, non-flammable, and ready to use.



PTFE TAPE

WRAS Approval No. 130750. Suitable for potable water & oxygen BS7786:2006 Grade L.



THREAD SEALING TAPE

PART NUMBER	DESCRIPTION
PTFE TAPE	12 m x 12 mm x 0.075 mm

2900