









Bonomi Group

The Bonomi Group, with corporate headquarters in Italy and technical sales offices in the United Kingdom, Germany, Russia, North America and India is a global organisation specialising in the production of valves and actuators.







UK Actuated Valve Workshop and Warehouse

Bonomi (UK) Ltd

Bonomi (UK) Ltd, established in 1999, offer a complete range of products and complementary services for the flow control industry.

This brochure offers just an overview; if you cannot find what you are looking for please contact the sales office for our complete product catalogue.









HYDRAULIC COMPONENTS










Contents











BRESCIANE







Services

Supporting

Walpres







703000



Full bore stainless steel AISI 316-CF8M ball valve, F/F threading, ISO 5211 Direct Mount, Antistatic Device.

700000



Full bore stainless steel AISI 316-CF8M ball valve, F/F threading. ISO Mounting Pad.

710000





Three piece stainless steel AISI 316-CF8M, full bore ball valve. ISO Mounting Pad.

713000



Three piece carbon steel ASTM WCB, full bore ball valve. ISO Mounting Pad.

600105



Butterfly valve Wafer type PN16, body in cast iron G250+Epoxy painting, EPDM seat. (NBR and VITON available).

600204



Butterfly valve LUG type PN16, body in ductile iron GGG40+Epoxy painting, EPDM seat. (NBR and VITON available).

730003



Full bore flanged ball valve, PN16 in cast iron, according to EN 558 basic series 14 (DN 200 basic series 27).

772000/ 775000



Three way reduced bore, in stainless steel AISI 316-CF8M ball valve, four seats, female threads.

721000





Full bore flanged ball valve PN16, in stainless steel AISI 316-CF8M.

722000 Available FIRE SAFE version



Full bore flanged valve PN16 in carbon steel ASTM A105 - WCB.

Valpres



The company reserves the right to vary models and dimensions without notice.

These products are designed for industrial applications and are not suitable for sale to the general public.

PROCESS VALVES

760005 ANSI 150

762000 carbon steel WCB

761030 ANSI 300

761031 carbon steel WCB



Stainless steel AISI 316-CF8M ball valve, full bore, Fire Safe, Antistatic Device.

766000 ANSI 150

766001 carbon steel WCB

765000 PN16

765001 carbon steel WCB



Stainless steel AISI316 - CF8M ball valve, full bore, Fire Safe, Antistatic Device with ISO 5211 Direct Mount.

760000 PN16

760001 carbon steel WCB



Flanged PN16 / PN40 Stainless Steel AISI 316-CF8M ball valve, full bore, Fire Safe, Antistatic Device.

OIL & GAS DIVISION

This is just a small selection from our oil and gas division - Please contact the Bonomi sales office for support.

680000-2

Available with flanged ends welded ends or customized ends

Available welded body

FIRE SAFE ISO 10497



Trunnion mounted ball valve, Split Body to API6D/API 6A.

For technical advice contact the Bonomi sales office

780000-2

FIRE SAFE ISO 10497



Trunnion mounted ball valve Split Body to API6D/BS6364.

FIRE SAFE ISO 10497

DBB



Double Block and Bleed Valve, Floating ball valve Split Body or Top Entry to API6D/API608/ISO17292-BS6364 or Trunnion Split Body API6D/BS6364.









Venue I — IQNET —



03900000097



Explosion proof Limit Switch Box according to EExd IIB T4/T5/T6 standards.

Other Ex options are available (including I.S.).

03900000034



Compact corrosion resistant limit Switch Box.

NA34 Series



3/2 and 5/2 way Namur Solenoid Valves Ex options available.

Gearbox




De-clutchable gear operator for the manual override of double and single acting Pneumatic Actuators.

31600000005



31600000004





Special Executions





Locking Handle.



The company reserves the right to vary models and dimensions without notice. These products are designed for industrial applications and are not suitable for sale to the general public.

ACTUATORS



Pneumatic Actuators 0° - 90°. C & II 2 G/D c T6 APPROVED.



Pneumatic Actuators 0° - 180°. C E II 2 G/D c T6 APPROVED.



PTFE Coated Pneumatic Actuators. $\zeta \in \mathbb{C}$ II 2 G/D c T6 APPROVED.





Mini Electric Actuators.

For technical advice contact the Bonomi sales office.



Electric Actuators with Technopolymer Housing.



Electric Actuators with Die Cast Aluminium Housing.






Walbia









Pneumatically Actuated Wafer Ball Valves, Stainless Steel and Carbon Steel.



Pneumatically Actuated Wafer and Lugged Butterfly Valves.



Electrically Actuated Wafer and Lugged Butterfly Valves.



Pneumatically Actuated Three-Piece Stainless Steel Ball Valves.



Pneumatically Actuated Two-Way Ball Valves in Brass and Stainless Steel.



Electrically Actuated Three-Way High Pressure Ball Valves.



Electrically Actuated Two-Way Ball Valves in Stainless Steel.



Electrically Actuated
Three-Way Ball Valves in
Brass



Electrically and Pneumatically Actuated Stainless Steel Ball Valves, Full Bore, Split Body Type. Direct Mount.

ACTUATED SYSTEMS

THE ACTUATED VALVE WORKSHOP



- Pneumatic and Electric Actuators
- Single and Double Acting
- Comprehensive Range of Valves (Ex-Stock)
- · Fully Assembled and Tested

















BRASS BALL VALVES

1600



Full bore brass ball valve. Aluminium Handle - F/F. WRAS Approved.



Full bore ball valve for gas, F/F threaded, with yellow steel handle. BSEN331 1998.

6273

1601

Full bore brass ball valve, M/F threaded, with aluminium handle.



Full bore brass ball valve, F/F threaded, with aluminium T-handle.

2500 ISO



Full bore ball valve, F/F threaded, with ISO 5211 pad for actuator.

3110/3210



Diverter full bore valve. Female threaded. T/L Port, with steel handle and ISO 5211 pad for actuator.

5808



Stem extension for thermic insulated plants.

6100

1620



Locking device.

3500/3600



Three way full bore valve. Female threaded. T/L Port, with steel handle and ISO 5211 pad for actuator.

3730/3731



Chrome plated, with handle, F/F.



Chrome plated,



with handle, M/F.

Customised Component Solutions



YOUR DETAILS

Custom printed lever available on request

4504



Full bore ball valve, female threaded and male union tail for manifold, with aluminium T-handle.

5110

Full bore ball valve, F/F threaded, with drain hole and steel handle.

300100

Various lever colours available.

100000



Full bore check valve, F/F ISO 7/1 threaded.



Pressure reducing and regulating valve with balanced seat from ISO 7/1.
















If what you are looking for is not shown please contact the Bonomi sales office.

PFT1/PFT3







CAM FF (F/M)



ISO 16028.



Flat Face Couplings Stainless Steel ISO 16028.

PLTX

PAVX

PBV1



Screw Couplings Enerpac Interchange.

Agricultural Coupling Trailer Brake.

Flat Face Couplings









Quick Release Couplings Stainless Steel ISO A Norm.

BKH

PVS1/PVS3/PVM



Hydraulic High Pressure 2 Way Ball Valves.

SKH

Hydraulic High Pressure 2 Way Ball Valves.

Quick Release Couplings



Premier ISO A Norm.

ISO A Norm.





Quick Release Couplings ISO B Norm.

Hydraulic 316 Stainless Steel High Pressure 2 Way Ball Valves.



Hydraulic 2 Way Ball Valves With SAE Flanges.

10

PBVM

PPV3



Quick Release Couplings - Brass

Push-Pull Quick Release Couplings





Quick Release Couplings - Stainless Steel ISO B Norm.

PVV3

PBVX

BK3/SK3



Hydraulic High Pressure 3 Way Diverter Ball



DV / DRV

Hydraulic Multiway Ball Valves 3 Way & 4 Way.

TGW



ISO B Norm.





Inline Check Valve



Hydraulic Check Valves in Carbon and Stainless Steel options.



Flow Control & Needle Valves. Uni & Bi Directional.





Screw Couplings

Gromelle Interchange.





Quick Release Screw Couplings.







INDUSTRIAL VALVES

Exclusive Official UK distributor for

Valves for district heating and cooling applications.

- Stainless Steel Balancing Valves



Exclusive UK distributor for









Stainless Steel Flanges.

IDRJA Check Valves 304 and 316 Stainless Steel,

Stainless Steel Suction and Discharge Manifolds, 2 Pump, 3 Pump and 4 Pump.

WRAS Approved.

ARMATUREN



Packaged Plate Heat Exchanger Set.



Triple Offset Metallic Seated Butterfly Valves.



Safety Valves ASME Code Section VIII -Division 1 UV - Stamp NB - Stamp to AP1526.





Metal and plastic measurement, control and regulation valves.

Honeywell

Ultravalve specialise in the testing of RPZ valves. Every engineer is WTI certified, CSCS approved, hold water hygiene cards and have been DBS (Disclosure & Barring Service) previously called CRB. Ultravalve are Constructionline, Safe Contractor and Achilles approved.






Flanged Stainless Steel

Self Cleaning Filters.

Pressure Reducing Valves.











UK Locations

Bonomi (UK) Ltd

The Fluid Power Centre, Watling Street, Nuneaton, Warwickshire, CV11 6BQ Tel: +44 (0)24 7635 4535 Fax: +44 (0)24 7635 4143 sales@bonomi.co.uk www.bonomi.co.uk

Ultravalve Ltd

Diamond Works, Units 11, 13 and 2a Maple Tree Lane, Halesowen, West Midlands, B63 2BN Tel: 01384 411888 Fax: 01384 411114 sales@ultravalve.co.uk www.ultravalve.co.uk



