EXTRAFLEX REINFORCED PVC WATER HOSE

GHY Series













Extraflex is perhaps the most versatile hose available today with its unique low temperature characteristics and outstanding flexibility in any climatic condition.

This abrasion resistant hose is reinforced with high tensile polyester cord and the first choice of the Professional in any market sector. Extraflex is already a familiar sight in demanding applications throughout Europe. Look for the distinctive yellow colour and brand mark on every coil.

The above specification far exceeds the requirements of British Standard BS 3746 for water hoses.

Key Features:

- High flexibility.
- Silicone free.
- Abrasion resistance good.
- Made from Cadmium free materials.
- Kink resistance good.
- Outstanding all year round flexibility.
- Polyester fibre reinforcement.
- Premium quality inner.
- Exceeds BS3746: 1990.

Sizes:

Available in 25m and 50m coils 12.5mm, 19mm & 25mm ID

Colours:

Product Ref

GHY12

GHY19

GHY25

Yellow with black inner









Internal Diameter	External Diameter	Minimum Working Pressure	Minimum Burst Pressure	Weight per Metre
12.5mm	17.5mm	10 Bar	30 Bar	0.144 Kg
19.25mm	25.5mm	8 Bar	24 Bar	0.298 Kg
25mm	32.5mm	6 Bar	18 Bar	0.440 Kg



- 1. DEHP free PVC inner
- 2. Polyester fiber reinforcement
- 3. DEHP free PVC outer



Applications:

- Watering
- Agriculture Irrigation
- Industrial use
- Horticulture