

# BAND-IT®



## Selectively Coated Ball-Lok Ties

*Manufactured in the UK from 316 Stainless Steel*



Underwriters Laboratories Listing  
on this product.



- Self locking operation for fast, easy application
- Two widths – 4.6mm & 7.9mm
- 316 Stainless steel with Nylon 11 coating
- Corrosion, UV and weather resistant
- Smooth inside diameter
- Zero halogen, low smoke

### K502 Ball-Lok Tool with automatic cut-off



- Quick and easy installation
- Adjustable tension
- Side loading and automatic tail cut-off

### KE922 Ball-Lok Tool with manual cut-off



- Tensions and cuts ties up to 12mm wide
- To apply coated or uncoated Ball-Lok ties
- Side loading

**Selectively Coated Ball-Lok Ties**

# Total Fastening Solutions

## Selectively Coated Ball-Lok Ties



### 316 Stainless Steel Selectively Coated Ball-Lok Ties Packed in bags of 100

PART NUMBER	MAX. BUNDLE DIAMETRE		APPROX LENGTH		APPROX WIDTH		APPROX WEIGHT PER 100		MIN. LOOP TENSILE STRENGTH		UL LISTED
	INCH	MM	INCH	MM	INCH	MM	LBS	KGS	LBS	N	
KE0618	1.2	30	5.9	150	0.18	4.6	0.55	0.25	100	445	UL LISTED
KE0628	2.0	50	7.9	201			0.62	0.28			
KE0638	2.7	69	10.2	259			0.75	0.34			
KE0648	4.0	102	14.2	360			1.01	0.46			
KE0658	6.0	152	20.4	520			1.41	0.64			
KE0668	8.0	203	26.8	679			1.80	0.82			
KE0678	10.0	254	33.0	838			2.33	1.06			
KE0818	1.2	30	5.9	150	0.31	7.9	1.02	0.46	120	534	UL LISTED
KE0828	2.0	50	7.9	201			1.16	0.53			
KE0838	2.7	69	10.2	259			1.50	0.68			
KE0848	4.0	102	14.2	360			1.78	0.81			
KE0858	6.0	152	20.4	520			2.46	1.12			
KE0868	8.0	203	26.8	679			3.17	1.44			
KE0878	10.0	254	33.0	838			3.83	1.74			

### Tool Weights

PART NUMBER	DESCRIPTION	WEIGHT		PACKAGE WEIGHT	
		LBS	KGS	LBS	KGS
K502	Ball-Lok tool	1.19	0.54	1.28	0.58
KE922	Manual Tool	1.23	0.56	1.41	0.64

For more detailed product information, please visit our website or call your sales team today!



©2014 BAND-IT IDEX  
All rights reserved.  
B725 04/2014

**www.band-it-idex.eu**  
BAND-ITUKSales.BAND-IT@idexcorp.com  
+44 (0)1246 477333