



Inspection - Detection



Rail Approval

FREEZER/2

FAULT DETECTION ON ELECTRONICS

Freezer/2 is a rapid cooling agent for locating faults in electronic components and for cooling thermally sensitive parts during soldering or calibration.

This product has been formulated without the use of any CFCs or HCFCs. EU F-Gas compliant. Non-Flammable*.

PRODUCT CODES / FILL SIZES



33182 / 400ml

APPLICATIONS

Suitable for instant fault finding on electronic equipment, such as printed circuit boards, transistors, resistors, condensers and intermittent dry joint connectors.

Other useful applications for Freezer include shrink fitting of metal assemblies and embrittlement of sticky substances (e.g. chewing gum) to facilitate removal.

DIRECTIONS

- The product should be sprayed directly onto the suspect component.
- If fault disappears, this confirms that the component is defective and should be replaced.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Gas at room temperature. Produces a temporary frosted finish
Odour	Slight ethereal odour
Specifications/Approvals	British Rail Catalogue No. 7/20505
SG @ 25°C	1.18
Pressure @ 25°C	4.9 Bar
Discharge rate	1.5 g/sec
Temperature range	Reduces component temperature to -50°C
Solubility	Soluble in some solvents, insoluble in water
Flammability	Non-flammable (according to directive 2008/47/EC)*
Flashpoint	Not applicable in sealed aerosol

* Remark regarding flammability: Although classified as nonflammable by GHS, DOT, IATA and IMDG and as measured by ASTM E-681 and ISO 10156, Solstice® Propellant (HFO-1234ze) can exhibit vapor flame limits at elevated temperatures. Solstice® Propellant has a very narrow flammable range (LFL-UFL) of 8.0-8.5 volume percent in air at one atmosphere under the following conditions:

- Temperature is 86°F (30°C), (and)
- Relative Humidity ≥50%, (and)
- High energy ignition source or open flame is present

Accordingly, CRC recommends that for use on energized electrical equipment the ambient temperature should be below 28C.

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1
Created: July 2019
Updated: October 2020

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

