TECHNICAL DATA





SILICONE ANTI-STICK

HEAVY DUTY SILICONE LUBRICANT

Silicone Anti-Stick is an anti-stick and slip inducing surface lubricant. It is based on a high purity, highly concentrated silicone oil for maximum materials compatibility, exceptional slip, and long-lasting performance.

It is a high concentration silicone lubricant for demanding applications with higher loads or increased speeds e.g. robotic picking lines, pallet conveyors guides, and close tolerance fitting of large bore water pipes.



Lubricants



WRAS Approved

PRODUCT CODES / FILL SIZES



APPLICATIONS

- Ideal for plastic-plastic surface lubrication
- Long-lasting for reduced relubrication requirements
- Excellent materials compatibility
- Use on rapidly oscillating sliding surfaces
- Excellent operation temperature range

DIRECTIONS

- Apply a light, even coating from 9" 12" (25 30 cm).
- Re-apply as necessary.





TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, colourless liquid
Odour	Hydrocarbon
SG @ 25°C	0.775
Pressure @ 25°C	2.6 Bar
Discharge rate	1.4 g/sec
Temperature range	Operational up to 200°C
Solubility	Soluble in solvents, insoluble in water
Flammability	Classified as extremely flammable under current EC Regulations
Flashpoint	Not applicable in sealed aerosol

MATERIALS COMPATIBILITY

OK CAUTION NOT OK

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 3.1 Created: July 2019 Updated: October 2020

CRC Industries UK Ltd. Wylds Road,Bridgwater Somerset, TA6 4DD United Kingdom

Company Registered No. 04910479

t +44 (0)1278 727200 f +44 (0)1278 425644 e sales.uk@crcind.com w www.ambersil.com

VAT No. GB 821 5195 42



bsi. 9001 Quality Management