

Tie-Lok® Ties



BAND-IT® Tie-Lok® ties offer a unique, dimple lock with a smooth ID and a low profile.

This clamp provides fast, consistent and reliable clamping tension. Used in many industries such as automotive, cable bundling and identification.

- Locks under full tension – no slip-back
- Low profile buckle
- A strong patented dimple lock
- Available in 6.35mm or 4.5mm widths
- Available in 304 or 316 grade stainless steel options
- Great for cable bundling or ID attachment



A920 (Tie-Lok) / A910 (Mini Tie-Lok) / A940 (Ultra Lok)

See pages 26-29 for full details on TOOLS and their specifications.

Tie-Lok® Ties

PART NUMBER	MATERIAL	WIDTH		LENGTH		PACKAGE WEIGHT		MAX DIAMETER SINGLE WRAP		MINIMUM LOOP TENSILE STRENGTH	PACKAGE QTY
		IN	MM	IN	MM	LBS	KG	IN	MM	LBS	BAGS
AS211	304 SS	0.25	6.4	10	254	1.2	0.6	2	51	250	100
AS212	304 SS	0.25	6.4	16.5	419	1.8	0.9	4	101	250	100
AS213	304 SS	0.25	6.4	22.5	572	2.6	1.2	6	152	250	100
AS214	304 SS	0.25	6.4	29	737	3.3	1.5	8	203	250	100
AS215	304 SS	0.25	6.4	35	889	3.9	1.8	10	254	250	100
AS411	316 SS	0.25	6.4	10	254	1.2	0.6	2	21	250	100
AS412	316 SS	0.25	6.4	16.5	419	1.8	0.9	4	101	250	100
AS413	316 SS	0.25	6.4	22.5	572	2.6	1.2	6	152	250	100
AS414	316 SS	0.25	6.4	29	737	3.3	1.5	8	203	250	100
AS415	316 SS	0.25	6.4	35	889	3.9	1.8	10	254	250	100



Mini Tie-Lok® Ties

PART NUMBER	MATERIAL	WIDTH		LENGTH		PACKAGE WEIGHT		MAX DIAMETER SINGLE WRAP		MINIMUM LOOP TENSILE STRENGTH	PACKAGE QTY
		IN	MM	IN	MM	LBS	KGS	IN	MM	LBS	BAGS
AS221	304 SS	0.177	4.5	7	165	0.7	0.38	1	21	100	100
AS222	304 SS	0.177	4.5	10	254	0.9	0.38	2	51	100	100
AS223	304 SS	0.177	4.5	16	419	1.4	0.38	4	102	100	100
AS224	304 SS	0.177	4.5	22.5	572	1.9	0.38	6	152	100	100
AS225	304 SS	0.177	4.5	29	737	2.4	0.38	8	203	100	100
AS421	316 SS	0.177	4.5	7	165	0.7	0.38	1	25	100	100
AS422	316 SS	0.177	4.5	10	254	0.9	0.38	2	51	100	100
AS423	316 SS	0.177	4.5	16	419	1.4	0.38	4	102	100	100
AS424	316 SS	0.177	4.5	22.5	572	1.9	0.38	6	152	100	100
AS425	316 SS	0.177	4.5	29	737	2.4	0.38	8	203	100	100

