

VALUSTRAP™ – Any Austenitic Stainless Steel Band



- A non-magnetic 200-300 AA grade stainless steel strapping
- Used for securing light weight signs, pipe insulation, cable bundling, and a variety of other lightweight fastening applications
- Good corrosion resistance



C001 / C075 / C400

See pages 26-29 for full details on **TOOLS** and their specifications.

Valustrap™

Austenitic Stainless Steel • Thickness 0.015" (0.38mm)

100Ft. Roll (30.5M)					300Ft. Roll (91.5M)		
PART NUMBER	WIDTH		WEIGHT		PART NUMBER	WEIGHT	
	IN.	MM	LBS	KGS		LBS	KGS
C133	3/8	9.53	2.2	1.0	C123	5.7	2.6
C134	1/2	12.70	2.9	1.3	C124	7.7	3.5
C135	5/8	15.88	3.6	1.7	C125	9.7	4.4
C136	3/4	19.05	4.4	2.0	C126	11.7	5.3

Available in mill coil lengths. All sizes in standard cardboard packaging

Valustrap™ Plus 100Ft. Roll (30.5M)

Austenitic Stainless Steel • Thickness 0.020" (0.51mm)

PART NUMBER	WIDTH		WEIGHT	
	IN.	MM	LBS	KGS
C191	3/8	9.53	2.9	1.3
C181	1/2	12.70	3.8	1.7
C171	5/8	15.88	5.6	2.5
C161	3/4	19.05	5.7	2.6

Available in mill coil lengths

304 Stainless Steel Band 200Ft. Roll (61M)

304 Stainless Steel • Thickness 0.015" (0.38mm)

PART NUMBER	WIDTH		WEIGHT	
	IN.	MM	LBS	KGS
C903	3/8	9.53	4.4	2.0
C904	1/2	12.70	5.8	2.6
C905	5/8	15.88	7.3	3.2
C906	3/4	19.05	8.8	3.9

Available in mill coil lengths



Valustrap™

Valuclips™ Pack Qty – 100 • Austenitic Stainless Steel

PART NUMBER	WIDTH		WEIGHT	
	IN.	MM	LBS	KGS
C153	3/8	9.53	0.6	0.3
C154	1/2	12.70	1.1	0.5
C155	5/8	15.88	1.2	0.5
C156	3/4	19.05	2.1	0.9



Valuclick™

Ultra-Lok® Clamping System




Ultra-Lok® Free
End Clamps and
Buckles

The stronger and faster alternative to band and buckle

Designed for quick installation, tightest clamping force and gap-free inside diameter. The strongest band clamping system available.

- Smooth inside diameter designed to eliminate leak paths
- Single or double wrapped 1/4 hardened 201SS for superior clamping strength
- Locks under full tension (no slip-back) maximizing clamping force
- Applied four times faster than band and buckle
- Consistent and repeatable tensioning
- Buckle is thicker and 2-3 times stronger than other clamps
- Buckle hood protects lock from snags
- Ideal for field repairs / heavy duty bundling / attachment of Brack-Its and equipment to poles, etc



UL4000 / UL9010

See pages 26-29 for full details on TOOLS and their specifications.

Ultra-Lok® Free End Clamps

Type 201 1/4 hardened stainless steel band • Thickness 0.030" (0.76mm)

PART NUMBER	CLAMP DIAMETER										
	SINGLE WRAP		DOUBLE WRAP		BAND WIDTH		LENGTH		WIDTH		PACKAGE QTY
	In	mm	In.	mm	In	mm	In	mm	Lbs	Kg	
UL2030	8.0	203.2	3.8	96.5	3/4	19.05	30	762	5.25	2.39	25
UL2042	11.8	299.7	5.7	144.8	3/4	19.05	42	1067	7.00	3.18	25
UL2060	17.5	444.5	8.6	218.4	3/4	19.05	60	1524	10.25	4.66	25
UL2084	25.2	640.1	12.4	315.0	3/4	19.05	84	2134	14.75	6.70	25
UL2120	36.6	929.6	18.2	462.3	3/4	19.05	120	3048	20.50	9.32	25
UL1018	3.0	76.2	—	—	1/2	12.70	18	457	2.00	0.91	25
UL1024	5.0	127.0	—	—	1/2	12.70	24	610	2.75	1.25	25
UL1028	6.0	152.4	3.0	76.2	1/2	12.70	28	711	3.25	1.48	25
UL1032	7.0	177.8	3.5	88.9	1/2	12.70	32	813	3.50	1.59	25
UL1036	8.0	203.2	4.0	101.6	1/2	12.70	36	914	4.00	1.82	25
UL1046	11.0	279.4	5.5	139.7	1/2	12.70	46	1168	5.90	2.70	25
UL1056	14.0	355.6	7.0	177.8	1/2	12.70	56	1422	7.10	3.20	25
UL1070	18.0	457.2	9.0	228.6	1/2	12.70	70	1778	8.50	3.90	25
UL1086	22.0	558.8	11.0	279.4	1/2	12.70	86	2184	10.20	4.60	25
UL1096	25.0	635.0	12.5	317.5	1/2	12.70	96	2438	11.20	5.10	25
UL1106	28.0	711.2	14.0	355.6	1/2	12.70	106	2692	12.70	5.80	25
UL1116	31.0	787.4	15.5	393.7	1/2	12.70	116	2946	13.30	6.00	25

* 1/2" Bands will require M09387 shear plate fitted to UL9010 and UL4000 tools

Ultra-Lok® Free End Buckles

201 Stainless Steel • Pack Qty – 100

PART NUMBER	WIDTH		WEIGHT	
	IN.	MM	LBS	KGS
UB2549	1/2	12.70	2.4	1.1
UB2569	3/4	19.05	3.7	1.7